An ACI Standard

Code Requirements for the Design of Precast Concrete Diaphragms for Earthquake Motions (ACI 550.5-18) and Commentary (ACI 550.5R-18)

Reported by Joint ACI-ASCE Committee 550

VCI 550.5-18



American Concrete Institute

Always advancing



First Printing June 2018

ISBN: 978-1-64195-017-6

Code Requirements for the Design of Precast Concrete Diaphragms for Earthquake Motions (ACI 550.5-18) and Commentary (ACI 550.5R-18)

Copyright by the American Concrete Institute, Farmington Hills, MI. All rights reserved. This material may not be reproduced or copied, in whole or part, in any printed, mechanical, electronic, film, or other distribution and storage media, without the written consent of ACI.

The technical committees responsible for ACI committee reports and standards strive to avoid ambiguities, omissions, and errors in these documents. In spite of these efforts, the users of ACI documents occasionally find information or requirements that may be subject to more than one interpretation or may be incomplete or incorrect. Users who have suggestions for the improvement of ACI documents are requested to contact ACI via the errata website at http://concrete.org/Publications/DocumentErrata.aspx. Proper use of this document includes periodically checking for errata for the most up-to-date revisions.

ACI committee documents are intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. Individuals who use this publication in any way assume all risk and accept total responsibility for the application and use of this information.

All information in this publication is provided "as is" without warranty of any kind, either express or implied, including but not limited to, the implied warranties of merchantability, fitness for a particular purpose or non-infringement.

ACI and its members disclaim liability for damages of any kind, including any special, indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use of this publication.

It is the responsibility of the user of this document to establish health and safety practices appropriate to the specific circumstances involved with its use. ACI does not make any representations with regard to health and safety issues and the use of this document. The user must determine the applicability of all regulatory limitations before applying the document and must comply with all applicable laws and regulations, including but not limited to, United States Occupational Safety and Health Administration (OSHA) health and safety standards.

Participation by governmental representatives in the work of the American Concrete Institute and in the development of Institute standards does not constitute governmental endorsement of ACI or the standards that it develops.

Order information: ACI documents are available in print, by download, through electronic subscription, or reprint and may be obtained by contacting ACI.

Most ACI standards and committee reports are gathered together in the annually revised the ACI Collection of Concrete Codes, Specifications, and Practices.

American Concrete Institute 38800 Country Club Drive Farmington Hills, MI 48331 Phone: +1.248.848.3700

+1.248.848.3701

www.concrete.org

This is a preview. Click here to purchase the full publication.

ACI 550.5-18

Code Requirements for the Design of Precast Concrete Diaphragms for Earthquake Motions (ACI 550.5-18) and Commentary (ACI 550.5R-18)

An ACI Standard

Reported by Joint ACI-ASCE Committee 550

Larbi M. Sennour*, Chair

Lance Osborne, Secretary

Suzanne Aultman
Roger J. Becker*
Te-Lin Chung
Ned M. Cleland*
Manuel Conde Fuentes
Thomas J. D'Arcy*
William K. Doughty
Semeh Ibrahim El Ashri

Alvin C. Ericson

Mostafa Mohamed Gad Alla
Harry A. Gleich
Neil M. Hawkins†

Augusto H. Holmberg
L. S. Paul Johal
Jason J. Krohn*
Emily B. Lorenz

Kenneth A. Luttrell
Vilas S. Mujumdar
Clay J. Naito*
Clifford R. Ohlwiler
Victor F. Pizano-Thomen
Charles L. Pizzano
Jose I. Restrepo*
Sami H. Rizkalla

Mario E. Rodriguez*
Joseph C. Sanders*
James Schroder
John F. Stanton
P. Jeffrey Wang
Cloyd E. Warnes
Michael H. Weber

Special thanks to S. K. Ghosh and S. Nakaki for their contributions to this standard.

This standard describes code requirements for the design of precast concrete diaphragms subject to earthquake motions where used under the design provisions of ASCE/SEI 7-16 Section 12.10.3 and ACI 318. The response of precast concrete diaphragms under earthquake motions depends primarily on the strength, stiffness, and deformation capacities of the connectors and the reinforcement at joints between the precast concrete members. The seismic forces specified in ASCE/SEI 7 for the design of precast concrete diaphragms, their chords, and collectors in structures assigned to Seismic Design Category (SDC) C, D, E, or F are tied to force reduction factors specified in ASCE/SEI 7-16 Chapter 12, and to

ACI Committee Reports, Guides, and Commentaries are intended for guidance in planning, designing, executing, and inspecting construction. This document is intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. The American Concrete Institute disclaims any and all responsibility for the stated principles. The Institute shall not be liable for any loss or damage arising therefrom.

Reference to this document shall not be made in contract documents. If items found in this document are desired by the Architect/Engineer to be a part of the contract documents, they shall be restated in mandatory language for incorporation by the Architect/Engineer.

the shear overstrength provided by the connections and the reinforcement at joints specified in ASCE/SEI 7-16 Chapter 14. The shear overstrength depends on the design methodology, elastic or ductile, used for the diaphragm and targets elastic response for the maximum considered earthquake for shear connections regardless of the design option selected. The design option that can be used depends on the assigned design category and on the span and aspect ratio of the diaphragm. The selection of the design option is associated with minimum requirements for the tensile deformation capacity of the connections and the reinforcement at joints.

Keywords: connections; diaphragms; earthquake-resistant structures; precast concrete; seismic design.

ACI 550.5-18 was adopted June 6, 2018, and published June 2018.

Copyright © 2018, American Concrete Institute.

All rights reserved including rights of reproduction and use in any form or by any means, including the making of copies by any photo process, or by electronic or mechanical device, printed, written, or oral, or recording for sound or visual reproduction or for use in any knowledge or retrieval system or device, unless permission in



^{*}Diaphragm Subcommittee members who developed this code

[†]Diaphragm Subcommittee Chair