ACI 343.1R-12

Guide for the Analysis and Design of Reinforced and Prestressed Concrete Guideway Structures

Reported by Joint ACI-ASCE Committee 343



American Concrete Institute[®] Advancing concrete knowledge

This is a preview. Click here to purchase the full publication.



First Printing November 2012

American Concrete Institute® Advancing concrete knowledge

Guide for the Analysis and Design of Reinforced and Prestressed Concrete Guideway Structures

Copyright by the American Concrete Institute, Farmington Hills, MI. All rights reserved. This material may not be reproduced or copied, in whole or part, in any printed, mechanical, electronic, film, or other distribution and storage media, without the written consent of ACI.

The technical committees responsible for ACI committee reports and standards strive to avoid ambiguities, omissions, and errors in these documents. In spite of these efforts, the users of ACI documents occasionally find information or requirements that may be subject to more than one interpretation or may be incomplete or incorrect. Users who have suggestions for the improvement of ACI documents are requested to contact ACI via the errata website at www.concrete.org/committees/errata.asp. Proper use of this document includes periodically checking for errata for the most up-to-date revisions.

ACI committee documents are intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. Individuals who use this publication in any way assume all risk and accept total responsibility for the application and use of this information.

All information in this publication is provided "as is" without warranty of any kind, either express or implied, including but not limited to, the implied warranties of merchantability, fitness for a particular purpose or non-infringement.

ACI and its members disclaim liability for damages of any kind, including any special, indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use of this publication.

It is the responsibility of the user of this document to establish health and safety practices appropriate to the specific circumstances involved with its use. ACI does not make any representations with regard to health and safety issues and the use of this document. The user must determine the applicability of all regulatory limitations before applying the document and must comply with all applicable laws and regulations, including but not limited to, United States Occupational Safety and Health Administration (OSHA) health and safety standards.

Participation by governmental representatives in the work of the American Concrete Institute and in the development of Institute standards does not constitute governmental endorsement of ACI or the standards that it develops.

Order information: ACI documents are available in print, by download, on CD-ROM, through electronic subscription, or reprint and may be obtained by contacting ACI.

Most ACI standards and committee reports are gathered together in the annually revised ACI Manual of Concrete Practice (MCP).

American Concrete Institute 38800 Country Club Drive Farmington Hills, MI 48331 U.S.A. Phone: 248-848-3700 Fax: 248-848-3701

www.concrete.org

This is a preview. Click here to purchase the full publication.

ACI 343.1R-12

Guide for the Analysis and Design of Reinforced and Prestressed Concrete Guideway Structures

Reported by Joint ACI-ASCE Committee 343

Nur Yazdani Chair

Hossam M. Abdou Hamid Ahmady Sameh S. Badie Shrinivas B. Bhide Selvakumar Buvanendaran W. Gene Corley Om P. Dixit Mamdouh M. El-Badry Noel J. Everard Apostolos Fafitis Andrew J. Foden Amin Ghali Angel E. Herrera David Hieber Thomas T. C. Hsu Mohsen A. Issa Richard G. Janecek Bruce C. Kates^{*†} Zhongguo John Ma Barney T. Martin Jr.* Alan B. Matejowsky Amir Mirmiran Aftab A. Mufti Hani H. A. Nassif John P. Newhook Andrzej S. Nowak Claudia P. Pulido Ayman E. Salama Harold R. Sandberg Johan C. F. Schor Jeffrey L. Smith Khaled S. Soubra Steven L. Stroh Maria M. Szerszen Gamil S. Tadros Raj Valluvan^{*} Jim J. Zhao Qun Zhong-Brisbois^{*} Consulting members F. Arbabi John L. Carrato V. M. Davidge Tim Delis Mingzhu Duan Allan C. Harwood Jenn-Shin Hwang Clellon L. Loveall

*Indicates members of the subcommittee that prepared this guide.

[†]Subcommittee Chair.

The committee acknowledges C. A. Banchik, D. Bilow, K. Hjorteset, T. T. C. Hsu, A. S. Nowak, A. M. Okeil, G. S. Tadros, and K. Wongkaew for their contributions to this guide. A special acknowledgment is due to M. Y. Riad* for his significant contributions to this guide.

This guide presents a procedure for the design and analysis of reinforced and prestressed concrete guideway structures for public transit, and design guidance for elevated transit guideways. The engineer is referred to the appropriate highway and railway bridge design codes for items not covered in this document.

Limit state philosophy is applied to develop design criteria. A reliability approach is used in defining load combinations and deriving load and resistance factors. Different target reliability indexes (4.0 for design strength, 2.5 for serviceability design for cracking, and 2.0 for serviceability design for fatigue) and a service life of 75 years were used as the basis for safety analysis. A 75-year service life is consistent with the American Association of State Highway and Transportation Officials (AASHTO) Load and Resistance Factor Design (LRFD) Bridge Design Specifications.

Keywords: cracking; deformation; fatigue; guideway structures; precast concrete; prestressed concrete; prestressing loads; reinforced concrete; vibration.

ACI Committee Reports, Guides, and Commentaries are intended for guidance in planning, designing, executing, and inspecting construction. This document is intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. The American Concrete Institute disclaims any and all responsibility for the stated principles. The Institute shall not be liable for any loss or damage arising therefrom.

Reference to this document shall not be made in contract documents. If items found in this document are desired by the Architect/Engineer to be a part of the contract documents, they shall be restated in mandatory language for incorporation by the Architect/Engineer.

CONTENTS

Danielle D. Kleinhans

Secretary

Chapter 1—Introduction and scope, p. 2

1.1—Introduction 1.2—Scope

Chapter 2—Notation and definitions, p. 2

- 2.1—Notation
- 2.2—Definitions

Chapter 3—General design considerations, p. 4

- 3.1—Scope
- 3.2-Structural considerations
- 3.3—Functional considerations
- 3.4—Economic considerations
- 3.5-Urban impact
- 3.6—Transit operations
- 3.7—Structure/vehicle interaction
- 3.8—Geometries
- 3.9—Construction considerations
- 3.10-Rails and trackwork

ACI 343.1R-12 was adopted and published November 2012.. Copyright © 2012 American Concrete Institute.

All rights reserved including rights of reproduction and use in any form or by any means, including the making of copies by any photo process, or by electronic or mechanical device, printed, written, or oral, or recording for sound or visual reproduction or for use in any knowledge or retrieval system or device, unless permission in writing is obtained from the copyright proprietors.

Chapter 4—Loads, p. 17

- 4.1—General
- 4.2-Sustained loads
- 4.3—Transient loads
- 4.4-Loads due to volumetric changes
- 4.5-Exceptional loads
- 4.6—Construction loads

Chapter 5—Load combinations, load factors, and strength reduction factors, p. 23

- 5.1—Scope
- 5.2—Basic assumptions
- 5.3—Service load combinations
- 5.4—Strength load combinations

Chapter 6—Serviceability design, p. 24

- 6.1—General
- 6.2—Basic assumptions
- 6.3—Permissible stresses
- 6.4—Loss of prestress
- 6.5—Fatigue
- 6.6-Vibration and dynamic response
- 6.7—Deformations and rotations
- 6.8—Crack control

Chapter 7—Strength design, p. 29

- 7.1—General design and analysis considerations
- 7.2—Design for flexure and axial loads
- 7.3-Shear and torsion

Chapter 8—References, p. 31

CHAPTER 1—INTRODUCTION AND SCOPE

1.1—Introduction

The recommendations in this guide provide public agencies, consultants, and other interested personnel with comprehensive criteria for the design and analysis of concrete guideways for public transit systems. They differ from those given for bridge design and analysis in ACI 343R, American Association of State Highway and Transportation Officials (AASHTO) bridge specifications (AASHTO 2002, 2009, 2011, 2012), and the American Railway Engineering and Maintenance-of-Way Association (AREMA) *Manual of Railway Engineering* (AREMA 2012). This document provides guidance related chiefly to the design of guideway superstructures. For the design of substructure units, the reader is referred to other references such as AASHTO LRFD Bridge Design Specifications (AASHTO 2012).

1.2—Scope

Design criteria specifically recognize the unique features of concrete transit guideways—namely, guideway/vehicle interaction, rail/structure interaction, special fatigue requirements, and aesthetic requirements in urban areas. Criteria are based on current state-of-the-art practice for moderatespeed (up to 100 mph [160 km/h]) vehicles. Application of these criteria for advanced technologies other than those discussed in this guide requires an independent assessment.

AASHTO LRFD Bridge Design Specifications (AASHTO 2012) and ACI 343R are referenced for specific items not covered in these recommendations, including materials, construction considerations, and segmental construction.

CHAPTER 2—NOTATION AND DEFINITIONS

2.1—Notation

- A = exposed area of pier perpendicular to the direction of stream flow, ft² (m²)
- A_{cp} = area enclosed by the outer boundary of cross section, in.² (mm²)
- A_1 = area of longitudinal reinforcement in a member, in.² (mm²)
- A_o = lever arm area enclosed by the centerline of the shear flow, in.² (mm²)
- A_{oh} = area enclosed by the centerline of the outermost closed transverse torsion reinforcement, in.² (mm²)
- A_r = cross-sectional area of a rail, in.² (mm²)
- A_s' = area of compression reinforcement, in.² (mm²)
- A_t = area of one leg of a closed stirrup resisting torsion, in.² (mm²)
- A_{ν} = area of shear reinforcement, or area of shear reinforcement perpendicular to main reinforcement for deep beams, in.² (mm²)
 - = center-to-center distance of shorter dimension of closed rectangular stirrup, in. (mm)
- B = buoyancy

а

- BR = broken rail forces
- *b* = center-to-center distance of longer dimension of closed rectangular stirrup, in. (mm)
- C_D = flowing water drag coefficient
- C_d = horizontal wind drag coefficient
- CE = centrifugal force, lb (N)
- C_e = wind exposure coefficient
- C_g = wind gust effect coefficient
- COLFH = horizontal collision load, lb (N)
- COLFV = vertical collision load, lb (N)
- CR = forces due to creep in concrete, lb (N)
- CT = collision load, lb (N)
- c = clear concrete cover, in. (mm)
- DC = dead load, lb (N)
- DR = transit vehicle mishap load, due to vehicle derailment, lb (N)
- DW = dead load of wearing surfaces and utilities, lb (N)
- *d* = distance from extreme compressive fiber to centroid of longitudinal tension reinforcement, in. (mm)
- d_v = distance from centroid of tensile steel to centroid of concrete struts, in. (mm)
- E_c = modulus of elasticity of concrete, psi (MPa)
- E_{ci} = modulus of elasticity of concrete at transfer of prestress, psi (MPa)
- E_r = modulus of elasticity of rail steel, psi (MPa)
- E_s = modulus of elasticity of reinforcement, psi (MPa)
- *EH* = loads due to weight and pressure of soil, water in soil. or other material. lb (N)