

IN-LB

Inch-Pound Units

SI

International System of Units

An ACI Standard

Code Requirements for Seismic Analysis and Design of Liquid-Containing Concrete Structures (ACI 350.3-20) and Commentary

Reported by ACI Committee 350

ACI 350.3-20



American Concrete Institute
Always advancing

This is a preview. [Click here to purchase the full publication.](#)



Code Requirements for Seismic Analysis and Design of Liquid-Containing Concrete Structures (ACI 350.3-20) and Commentary

Copyright by the American Concrete Institute, Farmington Hills, MI. All rights reserved. This material may not be reproduced or copied, in whole or part, in any printed, mechanical, electronic, film, or other distribution and storage media, without the written consent of ACI.

The technical committees responsible for ACI committee reports and standards strive to avoid ambiguities, omissions, and errors in these documents. In spite of these efforts, the users of ACI documents occasionally find information or requirements that may be subject to more than one interpretation or may be incomplete or incorrect. Users who have suggestions for the improvement of ACI documents are requested to contact ACI via the errata website at <http://concrete.org/Publications/DocumentErrata.aspx>. Proper use of this document includes periodically checking for errata for the most up-to-date revisions.

ACI committee documents are intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. Individuals who use this publication in any way assume all risk and accept total responsibility for the application and use of this information.

All information in this publication is provided “as is” without warranty of any kind, either express or implied, including but not limited to, the implied warranties of merchantability, fitness for a particular purpose or non-infringement.

ACI and its members disclaim liability for damages of any kind, including any special, indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use of this publication.

It is the responsibility of the user of this document to establish health and safety practices appropriate to the specific circumstances involved with its use. ACI does not make any representations with regard to health and safety issues and the use of this document. The user must determine the applicability of all regulatory limitations before applying the document and must comply with all applicable laws and regulations, including but not limited to, United States Occupational Safety and Health Administration (OSHA) health and safety standards.

Participation by governmental representatives in the work of the American Concrete Institute and in the development of Institute standards does not constitute governmental endorsement of ACI or the standards that it develops.

Order information: ACI documents are available in print, by download, through electronic subscription, or reprint and may be obtained by contacting ACI.

Most ACI standards and committee reports are gathered together in the annually revised the ACI Collection of Concrete Codes, Specifications, and Practices.

American Concrete Institute
38800 Country Club Drive
Farmington Hills, MI 48331
Phone: +1.248.848.3700
Fax: +1.248.848.3701

www.concrete.org

Code Requirements for Seismic Analysis and Design of Liquid-Containing Concrete Structures (ACI 350.3-20) and Commentary

An ACI Standard

Reported by Joint ACI Committee 350

M. Reza Kianoush,* Chair

Jon B. Ardahl, Vice Chair

Andrew R. Minogue,† Secretary

Iyad M. Alsamsam
John W. Baker
Chuen-Shiow Chen*
Steven R. Close*
Mark W. Cunningham
Robert E. Doyle
Ronald R. Fiore

Anthony J. Galterio*
Carl A. Gentry*
Kenneth Ryan Harvey
Keith W. Jacobson
Edwina S. Lui
Daniel J. McCarthy
Kevin H. Monroe*

Khalid Motiwala
Jerry Parnes
Risto Protic*
Satish K. Sachdev
William C. Sherman†
Manwendra Sinha
Pericles C. Stivaros

Shashiprakash G. Surali
Lawrence M. Tabat*
John M. Tehaney*
Miroslav Vejvoda
William A. Wallace
Jeffrey S. Ward

Ahmed Hafez
Atis A. Liepins

Sanjay S. Mehta
Rolf P. Pawski

Nazar Sabti

Subcommittee Members

Consulting Members

William H. Backouse
Patrick J. Creegan
Anthony L. Felder
Charles S. Hanskat
Jerry A. Holland

David G. Kittridge
Dennis C. Kohl
Nicholas A. Legatos
Kyle S. Loyd
Carl H. Moon

Lawrence G. Mrazek
Javeed Munshi
Terry Patzias
Andrew R. Philip
Narayan M. Prachand

David M. Rogowsky
Lawrence J. Valentine

*Members of Seismic Provisions Subcommittee.

†Seismic Provisions Subcommittee Chair.

‡Seismic Provisions Subcommittee Secretary.

This Code prescribes procedures for the seismic analysis and design of liquid-containing concrete structures. These procedures address the loading side of seismic design and are intended to complement Section 1.1.9 and Chapter 13 of ACI 350-20.

Keywords: circular tanks; concrete tanks; convective component; earthquake resistance; environmental concrete structures; impulsive component; liquid-containing structures; rectangular tanks; seismic resistance; sloshing; storage tanks.

ACI Committee Reports, Guides, and Commentaries are intended for guidance in planning, designing, executing, and inspecting construction. This document is intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. The American Concrete Institute disclaims any and all responsibility for the stated principles. The Institute shall not be liable for any loss or damage arising therefrom.

Reference to this document shall not be made in contract documents. If items found in this document are desired by the Architect/Engineer to be a part of the contract documents, they shall be restated in mandatory language for incorporation by the Architect/Engineer.

ACI 350.3R-20 supersedes 350.3-06, became effective November 20, 2020, and was published October 2021.

Copyright © 2021, American Concrete Institute.

All rights reserved including rights of reproduction and use in any form or by any means, including the making of copies by any photo process, or by electronic or mechanical device, printed, written, or oral, or recording for sound or visual reproduction or for use in any knowledge or retrieval system or device, unless permitted in writing by the copyright proprietors.

This is a preview. Click here to purchase the full publication.

PREFACE

From the time it embarked on the task of developing an ACI 318-dependent code, ACI Committee 350 decided to expand on and supplement the seismic provisions for “Special Provisions for Seismic Design” to provide a set of thorough and comprehensive procedures for the seismic analysis and design of commonly used types of liquid-containing structures of circular and rectangular configurations. The committee’s decision was influenced by the recognition that liquid-containing structures are unique structures whose seismic design is not adequately covered by the leading national codes and standards. A seismic design subcommittee was appointed with the charge to implement the committee’s decision.

The seismic subcommittee’s work was guided by two main objectives:

- (1) Produce a self-contained set of procedures that would enable a practicing engineer to perform a full seismic analysis and design of a liquid-containing structure. These procedures should cover both aspects of seismic design: the “loading side,” which is the determination of the seismic loads based on the mapped risk-adjusted maximum considered earthquake spectral response accelerations at short periods (S_s) and 1 second (S_1) obtained from the Seismic Ground Motion maps (ASCE/SEI 7-16 Chapter 22) and the geometry of the structure; and the “resistance side,” which is the detailed design of the structure in accordance with the provisions of ACI 350-20, to resist those loads safely.
- (2) Establish the scope of the new procedures consistent with the overall scope of ACI 350-20. This required the inclusion of all types of tanks—rectangular as well as circular; and reinforced concrete as well as prestressed.

There are currently at least two national standards that provide detailed procedures for the seismic analysis and design of liquid-containing structures: ANSI/AWWA D110-13 (R18), which is limited to circular, prestressed concrete tanks; and ANSI/AWWA D115-17, which covers both rectangular and circular prestressed concrete tanks.

As the loading side of seismic design is outside the scope of ACI 318, it was decided to maintain this practice in ACI 350 as well. Accordingly, the basic scope, format, and mandatory language of Chapter 21 of ACI 318-11 were retained with only enough revisions to adapt the seismic provisions to environmental engineering structures. Provisions similar to Section 1.1.9 of ACI 318-11 are included in ACI 350. This approach offers at least two advantages:

- (1) Allows ACI 350 to maintain the ACI 318 practice of limiting its seismic design provisions to the resistance side only.
- (2) Makes it easier to update these seismic provisions to keep up with the frequent changes and improvements in the field of seismic hazard analysis and evaluation.

The forces due to earthquake determined in accordance with this Code are intended to be used in the determination of load effects due to earthquake, E , in accordance with Chapter 9 of ACI 350-20. The seismic force levels and R -factors included in this Code provide results at strength levels, such as those included for seismic design in the International Code Council (ICC) 2012 International Building Code (IBC 2012), particularly the applicable connection provisions of IBC 2012 as referenced in ASCE/SEI 7-16. When comparing these provisions with other documents defining seismic forces at allowable stress levels (for example, the 1997 Uniform Building Code [UBC-1997]), the seismic forces in this Code should be reduced by the applicable factors to derive comparable forces at allowable stress levels.

Users should note the following general design methods used in this Code, which represent the evolution of seismic design of liquid-containing structures over a number of years since ASCE (1984), as follows:

- (a) Instead of assuming a rigid tank for which the acceleration is equal to the ground acceleration at all locations, this Code assumes amplification of response due to natural frequency of the tank.
- (b) The response modification factor is included.
- (c) Rather than combining impulsive and convective modes by algebraic sum, this Code combines these modes by square-root-sum-of-the-squares.
- (d) The effects of vertical acceleration are included.
- (e) An effective mass coefficient applicable to the mass of the walls is included.

For further information on seismic behavior of liquid-containing structures, refer to Housner (1957, 1963b). For fluids other than water, refer to Veletsos and Shivakumar (1997).

CONTENTS**PREFACE, p. 2****CHAPTER 1—GENERAL REQUIREMENTS, p. 4**

- 1.1—Scope, p. 4
- 1.2—Notation, p. 4
- 1.3—Definitions, p. 10

CHAPTER 2—TYPES OF LIQUID-CONTAINING STRUCTURES, p. 11

- 2.1—Ground-supported structures, p. 11
- 2.2—Pedestal-mounted structures, p. 12

CHAPTER 3—GENERAL CRITERIA FOR ANALYSIS AND DESIGN, p. 13

- 3.1—Dynamic characteristics, p. 13
- 3.2—Design loads, p. 13
- 3.3—Design requirements, p. 13

CHAPTER 4—EARTHQUAKE DESIGN LOADS, p. 14

- 4.1—Earthquake pressures above base of tank wall, p. 14
- 4.2—Application of site-specific response spectra, p. 17

CHAPTER 5—EARTHQUAKE LOAD DISTRIBUTION, p. 19

- 5.1—General, p. 19
- 5.2—Shear transfer, p. 19
- 5.3—Dynamic force distribution above base of tank wall, p. 21

CHAPTER 6—STRESSES, p. 26

- 6.1—Rectangular tanks, p. 26
- 6.2—Circular tanks, p. 26

CHAPTER 7—FREEBOARD, p. 27

- 7.1—Wave oscillation, p. 27

CHAPTER 8—EARTHQUAKE-INDUCED EARTH PRESSURES, p. 32

- 8.1—General, p. 32
- 8.2—Limitations, p. 33
- 8.3—Alternative methods, p. 33

CHAPTER 9—DYNAMIC MODEL, p. 34

- 9.1—General, p. 34
- 9.2—Rectangular tanks (Type 1), p. 36
- 9.3—Circular tanks (Type 2), p. 40
- 9.4—Seismic response coefficients C_b , C_e , and C_b , p. 44
- 9.5—Site-specific seismic response coefficients C_b , C_e , and C_b , p. 45
- 9.6—Effective mass coefficient ϵ , p. 46
- 9.7—Pedestal-mounted tanks, p. 46

CHAPTER 10—COMMENTARY REFERENCES, p. 47**APPENDIX A—DESIGN METHOD, p. 49**

- A.1—General outline of design method, p. 49

CODE

CHAPTER 1—GENERAL REQUIREMENTS

1.1—Scope

This Code describes procedures for the design of liquid-containing concrete structures subjected to seismic loads. These procedures shall be used in accordance with Chapter 13 of **ACI 350-20**.

1.2—Notation

A_s	= cross-sectional area of prestressed and non-prestressed steel reinforcement, in. ² (mm ²)
b	= ratio of vertical to horizontal design acceleration
B	= inside dimension (length or width) of a rectangular tank, perpendicular to the direction of the ground motion being investigated, ft (m)
C_s , C_b , and C_t	= period-dependent seismic response coefficients (9.4 , 9.5)
C_b , C_w	= coefficients for determining the fundamental frequency of the tank-liquid system (Eq. (9.3.4b) and Fig. 9.3.4b)
C_s	= period-dependent seismic coefficient
d_{max}	= maximum vertical displacement of an oscillating wave measured from the liquid surface at rest, ft (m)
D	= inside diameter of circular tank, ft (m)
EBP	= excluding base pressure (datum line just above the base of the tank wall)

COMMENTARY

CHAPTER R1—GENERAL REQUIREMENTS

R1.1—Scope

This Code is a companion Code to Chapter 13 of the American Concrete Institute, “Code Requirements for Environmental Engineering Concrete Structures (ACI 350-20) and Commentary (ACI 350R-20).”

This Code provides requirements for the designer of liquid-containing concrete structures for computing seismic forces that are to be applied to the particular structure. The designer should also consider the effects of seismic forces on components outside the scope of this Code, such as piping, equipment (for example, clarifier mechanisms) and connecting walkways where vertical or horizontal movements between adjoining structures or surrounding backfill could adversely influence the ability of the structure to function properly (**NSF 1981**). Moreover, seismic forces applied at the interface of piping or walkways with the structure may also introduce appreciable flexural or shear stresses at these connections.

The hydrodynamic forces described in **ACI 350.3** can be used in design of liquid-containing concrete structures other than environmental structures if the licensed design professional or another reference standard chooses to use or refer to it.

The operational conditions used to calculate the seismic forces determined by this Code need to be evaluated by the licensed design professional. Considerations such as normal operational liquid levels, and potential for a tank or cells within a tank to be empty during a seismic event should be included. It is common to consider several loading conditions when designing for seismic loading, such as with the liquid at normal operating levels and with the tank or individual tank cells empty.

R1.2—Notation

For C_s , refer to **ASCE/SEI 7-16** Section 12.8.1.

EBP refers to the hydrodynamic design in which it is necessary to compute the overturning of the wall with respect to the top of the tank floor, excluding base pressure (that is, excluding the pressure on the floor itself). EBP