ACI 350.5M-12

(metric)

Specifications for Environmental Concrete Structures

An ACI Standard

Reported by ACI Committee 350



American Concrete Institute®



Specifications for Environmental Concrete Structures

Copyright by the American Concrete Institute, Farmington Hills, MI. All rights reserved. This material may not be reproduced or copied, in whole or part, in any printed, mechanical, electronic, film, or other distribution and storage media, without the written consent of ACI.

The technical committees responsible for ACI committee reports and standards strive to avoid ambiguities, omissions, and errors in these documents. In spite of these efforts, the users of ACI documents occasionally find information or requirements that may be subject to more than one interpretation or may be incomplete or incorrect. Users who have suggestions for the improvement of ACI documents are requested to contact ACI via the errata website at www.concrete.org/committees/errata.asp. Proper use of this document includes periodically checking for errata for the most up-to-date revisions.

ACI committee documents are intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. Individuals who use this publication in any way assume all risk and accept total responsibility for the application and use of this information.

All information in this publication is provided "as is" without warranty of any kind, either express or implied, including but not limited to, the implied warranties of merchantability, fitness for a particular purpose or non-infringement.

ACI and its members disclaim liability for damages of any kind, including any special, indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use of this publication.

It is the responsibility of the user of this document to establish health and safety practices appropriate to the specific circumstances involved with its use. ACI does not make any representations with regard to health and safety issues and the use of this document. The user must determine the applicability of all regulatory limitations before applying the document and must comply with all applicable laws and regulations, including but not limited to, United States Occupational Safety and Health Administration (OSHA) health and safety standards.

Participation by governmental representatives in the work of the American Concrete Institute and in the development of Institute standards does not constitute governmental endorsement of ACI or the standards that it develops.

Order information: ACI documents are available in print, by download, on CD-ROM, through electronic subscription, or reprint and may be obtained by contacting ACI.

Most ACI standards and committee reports are gathered together in the annually revised ACI Manual of Concrete Practice (MCP).

American Concrete Institute 38800 Country Club Drive Farmington Hills, MI 48331 U.S.A.

Phone: 248-848-3700 Fax: 248-848-3701

www.concrete.org

ISBN-13: 978-0-87031-815-3 ISBN: 0-87031-815-2

Specifications for Environmental Concrete Structures

An ACI Standard

Reported by ACI Committee 350

Satish K. Sachdev*, Chair Jon B. Ardahl†, Vice Chair

John W. Baker*, Secretary

Iyad M. Alsamsam Steven R. Close* Robert E. Doyle Anthony L. Felder* Carl A. Gentry Charles S. Hanskat* Kenneth R. Harvey Paul Hedli Keith W. Jacobson M. Reza Kianoush Ramon E. Lucero Daniel J. McCarthy Andrew R. Minogue Khalid Motiwala Javeed Munshi Jerry Parnes Risto Protic William C. Sherman* Lawrence M. Tabat* William A. Wallace Subcommittee members
Erik Lederman
Kyle S. Loyd
Edwin W. Neely
Victor M. Pavon
David R. Poole
Shashiprakash Surali
Bryan T. Wood

Consulting members
William H. Backous

Walter N. Bennett
Patrick J. Creegan
Jerry A. Holand
William J. Irwin
Dov Kaminetzky
David G. Kittridge
Dennis C. Kohl
Nicholas A. Legatos
Carl H. Moon
Lawrence G. Mrazek
Terry Patzias
Andrew R. Philip

Note: Special acknowledgement to Vijai Prakash Gupta, Larry Kaiser, William Moore, and Paul St. John for their contributions to this document.

This specification is a Reference Specification that the Architect/ Engineer can make applicable to a construction project by citing it in the Project Specifications. The Architect/Engineer supplements the provisions of this Reference Specification as needed by designating or specifying individual project requirements.

The document covers materials and proportioning of concrete; reinforcement and prestressing reinforcement; production, placing, finishing, and curing of concrete; formwork design and construction; and shotcrete. Methods of treatment of joints and embedded items, repair of surface defects, and finishing of formed and unformed surfaces are specified. Separate sections are devoted to architectural concrete, mass concrete, and internal and external post-tensioned prestressed concrete. Provisions governing testing, evaluation, and acceptance of concrete as well as acceptance of the structure are included.

Keywords: admixtures; aggregates; air entrainment; architectural concrete; compressive strength; consolidation; curing; density; durability; evaluation; environmental concrete; finishes; floors; formwork (construction); grouting; inspection; joints; mass concrete; mixture proportioning; posttensioned prestressed concrete; prestressing reinforcement; reinforcing steels; reshoring; shoring; subgrades; tolerances.

CONTENTS

Section 1—General requirements, p. 3

1.1—Scope

1.1.1—Work specified

- 1.1.2—Work not specified
- 1.2—Definitions
- 1.3—Reference standards
- 1.4—Standards-producing organizations
- 1.5—Submittals
- 1.5.1—General
- 1.5.2—Testing agency reports
- 1.6—Quality assurance
- 1.6.1—General
- 1.6.2—Testing agencies
- 1.6.3—Testing responsibilities of Contractor
- 1.6.4—Testing responsibilities of Owner's Testing Agency
- 1.6.5—Tests on hardened concrete in-place
- 1.6.6—Evaluation of concrete strength tests
- 1.6.7—Acceptance of concrete strength
- 1.6.8—Field acceptance of concrete
- 1.7—Acceptance of structure
- 1.7.1—General
- 1.7.2—Dimensional tolerances

ACI 350.5M-12 became effective October 5, 2012, and was published April 2013. Copyright © 2013 American Concrete Institute.

All rights reserved including rights of reproduction and use in any form or by any means, including the making of copies by any photo process, or by electronic or mechanical device, printed, written, or oral, or recording for sound or visual reproduction or for use in any knowledge or retrieval system or device, unless permission in

This is a preview. Click here to purchase the full publication.

Subcommittee members who developed this document.

[†]Subcommittee chair during development of this document.

- 1.7.3—Appearance
- 1.7.4—Strength of structure
- 1.7.5—Durability
- 1.8—Protection of in-place concrete
- 1.8.1—Loading and support of concrete
- 1.8.2—Protection from mechanical injury

Section 2—Formwork and formwork accessories, p. 10

- 2.1—General
- 2.1.1—Description
- 2.1.2—Submittals
- 2.2—Products
- 2.2.1—Materials
- 2.2.2—Performance and design requirements
- 2.2.3—Fabrication and manufacture
- 2.3—Execution
- 2.3.1—Construction and erection of formwork
- 2.3.2—Removal of formwork
- 2.3.3—Reshoring and backshoring
- 2.3.4—Strength of concrete required for removal of formwork
 - 2.3.5—Field quality control

Section 3—Reinforcement and reinforcement supports, p. 12

- 3.1—General
- 3.1.1—Submittals, data, and drawings
- 3.1.2—Materials delivery, storage, and handling
- 3.2—Products
- 3.2.1—Materials
- 3.2.2—Fabrication
- 3.3—Execution
- 3.3.1—Preparation
- 3.3.2—Placement

Section 4—Joints and accessories, p. 16

- 4.1—General
- 4.1.1—Description
- 4.1.2—Submittals
- 4.2—Products
- 4.2.1—Materials
- 4.2.2—Performance and design requirements
- 4.3—Execution
- 4.3.1—General
- 4.3.2—Construction joints and other bonded joints
- 4.3.3—Contraction joints
- 4.3.4—Expansion joints
- 4.3.5—Waterstops
- 4.3.6—Smooth dowels

Section 5—Concrete mixtures, p. 18

- 5.1—General
- 5.1.1—Description
- 5.1.2—Submittals
- 5.1.3—Quality control
- 5.1.4—Materials storage and handling
- 5.2—Products

- 5.2.1—Materials
- 5.2.2—Performance and design requirements
- 5.2.3—Proportioning
- 5.3—Execution
- 5.3.1—Measuring, batching, and mixing
- 5.3.2—Delivery

Section 6—Handling, placing, and constructing, p. 22

- 6.1—General
- 6.1.1—Description
- 6.1.2—Submittals
- 6.1.3—Delivery, storage, and handling
- 6.2—Products
- 6.2.1—Materials
- 6.3—Execution
- 6.3.1—Preparation
- 6.3.2—Placement of concrete
- 6.3.3—Finishing formed surfaces
- 6.3.4—Finishing unformed surfaces
- 6.3.5—Curing and protection
- 6.3.6—Repair of surface defects

Section 7—Architectural concrete, p. 28

- 7.1—General
- 7.1.1—Description
- 7.1.2—Submittals
- 7.1.3—Quality assurance
- 7.1.4—Product delivery, storage, and handling
- 7.1.5—Project conditions
- 7.2—Products
- 7.2.1—Materials
- 7.2.2—Performance and design requirements
- 7.3—Execution
- 7.3.1—Preparation
- 7.3.2—Proportioning concrete mixtures
- 7.3.3—Consolidation
- 7.3.4—Formwork monitoring
- 7.3.5—Formwork removal
- 7.3.6—Repair of tie holes and surface defects
- 7.3.7—Finishing

Section 8—Mass concrete, p. 30

- 8.1—General
- 8.1.1—Description
- 8.1.2—Submittals
- 8.2—Products
- 8.2.1—Materials
- 8.2.2—Performance and design requirements
- 8.3—Execution
- 8.3.1—Placement
- 8.3.2—Curing and protection

Section 9—Internal post-tensioned concrete, p. 31

- 9.1—General
- 9.1.1—Description
- 9.1.2—Submittals
- 9.1.3—Ouality control

This is a preview. Click here to purchase the full publication.

- 9.1.4—Product handling and storage
- 9.2—Products
- 9.2.1—Materials
- 9.2.2—Proportioning of cementitious grout mixtures
- 9.2.3—Proportioning of epoxy grout mixtures
- 9.3—Execution
- 9.3.1—Field observations
- 9.3.2—Grouted tendon installation
- 9.3.3—Grouting
- 9.3.4—Unbonded tendon installation
- 9.3.5—Tendon tolerances
- 9.3.6—Concrete placement
- 9.3.7—Tensioning
- 9.3.8—Tendon finishing

Section 10—External prestressed wrapped concrete tanks, p. 38

- 10.1—General
- 10.1.1—Description
- 10.1.2—Submittals
- 10.1.3—Quality control
- 10.1.4—Product delivery, handling, and storage
- 10.2—Products
- 10.2.1—Materials
- 10.2.2—Proportioning of concrete and shotcrete mixtures
- 10.3—Execution
- 10.3.1—Placement

Notes to Specifier, p. 40

General notes

Foreword to Checklists, p. 40

Mandatory Requirements Checklist, p. 43

Optional Requirements Checklist, p. 44

Submittals Checklist, p. 52

(Mandatory portion follows)

SECTION 1—GENERAL REQUIREMENTS 1.1—Scope

- **1.1.1** *Work specified*—This specification covers cast-inplace environmental concrete and shotcrete. Provisions of this specification shall govern except where other provisions are specified in Contract Documents.
- **1.1.2** *Work not specified*—The following subjects are not in the scope of this specification:
 - a) Precast concrete products
 - b) Heavyweight shielding concrete
 - c) Slipformed paving concrete
 - d) Lightweight concrete
 - e) Shrinkage-compensating concrete
 - f) Terrazzo
 - g) Insulating concrete
 - h) Refractory concrete
 - i) Self-consolidating concrete
 - j) Slipformed concrete walls

k) Tilt-up concrete construction

1.2—Definitions

accepted—determined to be satisfactory by Architect/ Engineer.

ACI Concrete Field Testing Technician Grade I—a person who has demonstrated knowledge and ability to perform and record the results of ASTM standard tests on freshly mixed concrete and to make and cure test specimens. Such knowledge and ability shall be demonstrated by passing prescribed written and performance examinations and having credentials that are current with ACI.

ACI Reference Specification—a standardized mandatory-language document prescribing materials, dimensions, and workmanship incorporated by reference in contract documents with information in the Mandatory Requirements Checklist required to be provided in the Project Specification.

Architect/Engineer—Architect, Engineer, architectural firm, engineering firm, or architectural and engineering firm issuing Contract Documents, administering the Work under Contract Documents, or both.

architectural concrete—concrete designated by Architect/Engineer as requiring a specified appearance.

backshores—shores placed snugly under a concrete slab or structural member after the original formwork and shores have been removed from a small area at a time, without allowing the slab or member to deflect, or support its own weight or existing construction loads.

Contract Documents—a set of documents supplied by Owner to Contractor as the basis for construction; these documents contain contract forms, contract conditions, specifications, drawings, addenda, and contract changes.

Contractor—person, firm, or entity under contract for construction of the Work.

core wall—portion of the externally prestressed circular concrete tank wall placed in circumferential compression by prestressing.

cover coat—the layer or layers of shotcrete applied over the wire coat of an externally prestressed circular concrete tank wall.

diaphragm—thin metal sheet formed with vertical ribs embedded within the core wall of circular externally prestressed concrete tanks.

duct—a conduit (plain or corrugated) to accommodate prestressing steel for post-tensioned installation.

exposed to view—portion of structure that can be observed by the user during normal use.

finish coat—final layer of shotcrete placed on the cover coat of an externally prestressed circular concrete tank wall.

high-early-strength concrete—concrete that, through the use of ASTM C150 Type III cement or admixtures, is capable of attaining specified strength at an earlier age than normal concrete.

environmental engineering concrete structures—concrete structures intended for conveying, storing, or treating water, wastewater, or other nonhazardous liquids, and for secondary containment of hazardous materials.

Licensed Design Engineer—an individual engaged by the Contractor who is licensed to practice engineering as defined by the statutory requirements of the licensing laws of the state or jurisdiction in which the project is to be constructed.

mass concrete—a volume of concrete with dimensions large enough to require that measures be taken to prevent damage from the generation of heat and temperature gradients from hydration of the cementitious materials and attendant volume change.

normalweight concrete—concrete containing aggregate that conforms to ASTM C33 and that typically has a density between 2160 and 2560 kg/m³.

Owner—corporation, association, partnership, individual, public body, or authority for whom the Work is constructed.

permitted—accepted or acceptable to Architect/Engineer usually pertaining to a request by Contractor or when specified in Contract Documents.

plain mass concrete—mass concrete containing no reinforcement or less reinforcement than necessary to be considered reinforced mass concrete.

post-tensioning—a method of prestressing reinforced concrete in which tendons are tensioned after the concrete has attained a specified minimum in-place strength or a specified minimum age.

prestressing sheathing—a material encasing prestressing steel to prevent bonding of the prestressing steel with the surrounding concrete, to provide corrosion protection, and to contain the corrosion-inhibiting coating.

prestressed concrete—structural concrete in which internal stresses have been introduced to reduce potential tensile stresses in concrete resulting from loads.

Project Drawings—graphic presentation of project requirements.

Project Specifications—written documents that details requirements for the Work in accordance with service parameters and other specific criteria.

reference standards—standardized mandatory-language documents of a technical society, organization, or association, including codes of local or federal authorities, that are incorporated by reference in Contract Documents.

reinforced mass concrete—mass concrete containing adequate reinforcement, prestressed or nonprestressed, designed to act together with the concrete in resisting forces including those induced by temperature and shrinkage.

required—mandatory as prescribed in project specification or Contract Documents.

reshores—shores placed snugly under a stripped concrete slab or other structural member after the original forms and shores have been removed from a large area, thus requiring the new slab or structural member to deflect and support its own weight and existing construction loads applied before installation of the reshores.

shore—a temporary support designed to carry the weight of formwork, fresh concrete, and construction loads from above for recently built structures that have not developed full design strength.

strength test—the average of the compressive strengths of two cylinders made from the same sample of concrete and tested at 28 days or at test age designated for determination of specified compressive strength f_c .

submittal—document or material provided to Architect/ Engineer for review and acceptance.

wire coat—layer of shotcrete in direct contact with the prestressed reinforcement of an externally prestressed circular concrete tank wall.

wood formwork sheathing—the materials forming the contact face of forms; also called lagging or sheeting.

Work—the entire construction or separately identifiable parts thereof required to be furnished under Contract Documents.

wrapped prestressing system—prestressing system that applies a high tensile strand or wire, wound under tension by machines, around a circular concrete tank wall.

1.3—Reference standards

American Concrete Institute

117M-90—Standard Specifications for Tolerances for Concrete Construction and Materials

350M-06—Code Requirements for Environmental Engineering Concrete Structures

423.6-01—Specification for Unbonded Single-Strand Tendons and Commentary (withdrawn)

506.2-95—Specifications for Shotcrete

American Petroleum Institute

RP 13B-1-09—Recommended Practice for Field Testing Water-Based Drilling Fluids

American Welding Society

AWS D1.4-98—Structural Welding Code—Reinforcing Steel

ASTM International

A82/A82M-97a—Standard Specification for Steel Wire, Plain, for Concrete Reinforcement

A184/A184M-01—Standard Specification for Fabricated Deformed Steel Bar Mats for Concrete Reinforcement

A185/A185M-97—Standard Specification for Steel Welded Wire Reinforcement, Plain, for Concrete Reinforcement

A416/A416M-02—Standard Specification for Steel Strand, Uncoated Seven Wire for Prestressed Concrete

A421/A421M-02—Standard Specification for Uncoated Stress-Relieved Steel Wire for Prestressed Concrete

A475-98—Standard Specification for Zinc-Coated Steel Wire Strand

A496/A496M-97a—Standard Specification for Steel Wire, Deformed, for Concrete Reinforcement

A497-99—Standard Specification for Steel Welded Wire Reinforcement, Deformed, for Concrete Reinforcement

A615/A615M-03—Standard Specification for Deformed and Plain Billet-Steel Bars for Concrete Reinforcement

A641/A641M-98—Standard Specification for Zinc-Coated (Galvanized) Carbon Steel Wire

A648-95—Standard Specification for Steel Wire, Hard Drawn for Prestressing Concrete Pipe