ACI 376-11

# Code Requirements for Design and Construction of Concrete Structures for the Containment of Refrigerated Liquefied Gases and Commentary

An ACI Standard

Reported by ACI Committee 376



# **American Concrete Institute**<sup>®</sup>



First Printing May 2013

# Code Requirements for Design and Construction of Concrete Structures for the Containment of Refrigerated Liquefied Gases and Commentary

Copyright by the American Concrete Institute, Farmington Hills, MI. All rights reserved. This material may not be reproduced or copied, in whole or part, in any printed, mechanical, electronic, film, or other distribution and storage media, without the written consent of ACI.

The technical committees responsible for ACI committee reports and standards strive to avoid ambiguities, omissions, and errors in these documents. In spite of these efforts, the users of ACI documents occasionally find information or requirements that may be subject to more than one interpretation or may be incomplete or incorrect. Users who have suggestions for the improvement of ACI documents are requested to contact ACI via the errata website at www.concrete.org/committees/errata.asp. Proper use of this document includes periodically checking for errata for the most up-to-date revisions.

ACI committee documents are intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. Individuals who use this publication in any way assume all risk and accept total responsibility for the application and use of this information.

All information in this publication is provided "as is" without warranty of any kind, either express or implied, including but not limited to, the implied warranties of merchantability, fitness for a particular purpose or non-infringement.

ACI and its members disclaim liability for damages of any kind, including any special, indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use of this publication.

It is the responsibility of the user of this document to establish health and safety practices appropriate to the specific circumstances involved with its use. ACI does not make any representations with regard to health and safety issues and the use of this document. The user must determine the applicability of all regulatory limitations before applying the document and must comply with all applicable laws and regulations, including but not limited to, United States Occupational Safety and Health Administration (OSHA) health and safety standards.

Participation by governmental representatives in the work of the American Concrete Institute and in the development of Institute standards does not constitute governmental endorsement of ACI or the standards that it develops.

Order information: ACI documents are available in print, by download, on CD-ROM, through electronic subscription, or reprint and may be obtained by contacting ACI.

Most ACI standards and committee reports are gathered together in the annually revised ACI Manual of Concrete Practice (MCP).

American Concrete Institute 38800 Country Club Drive Farmington Hills, MI 48331 U.S.A. Phone: 248-848-3700 Fax: 248-848-3701

#### www.concrete.org

ISBN-13: 978-0-87031-814-6 ISBN: 0-87031-814-4

# This is a preview. Click here to purchase the full publication.

# Code Requirements for Design and Construction of Concrete Structures for the Containment of Refrigerated Liquefied Gases (ACI 376-11) and Commentary

An ACI Standard

# Reported by ACI Committee 376

Neven Krstulovic-Opara, Chair

Junius Allen Dale Berner Mike S. Brannan Hamish Douglas Charles S. Hanskat Humayun Hashmi Alan D. Hatfield Kare Hjorteset George C. Hoff Richard A. Hoffmann John Holleyoak Joseph Hoptay Thomas R. Howe Dajiu Jiang Jameel U. Khalifa Nicholas A. Legatos

Note: Special acknowledgment to Jeffrey Garrison for his contributions to this document.

**Keywords:** bund wall; commissioning; cryogenic; damage stability; decommissioning; earthquake design levels; fatigue; float out; floating storage unit; foundation heating; gravity base structure; impact loads; liners; liquefied natural gas; liquid stratification; permanent ballast; purging; refrigerated liquefied gas; reinforcement (cryogenic); tanks; thermal corner protection.

#### CONTENTS

INTRODUCTION
CHAPTER 1—GENERAL5
1.1—Scope
1.2—Quality assurance

ACI Committee Reports, Guides, and Commentaries are intended for guidance in planning, designing, executing, and inspecting construction. This document is intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. The American Concrete Institute disclaims any and all responsibility for the stated principles. The Institute shall not be liable for any loss or damage arising therefrom.

Reference to this document shall not be made in contract documents. If items found in this document are desired by the Architect/Engineer to be a part of the contract documents, they shall be restated in mandatory language for incorporation by the Architect/Engineer. Piotr D. Moncarz, Secretary

Praveen K. Malhotra Keith A. Mash Stephen Meier Robert W. Nussmeier Rolf P. Pawski Ramanujam S. Rajan William E. Rushing Jr. Robert W. Sward

#### Eric S. Thompson Sheng-Chi Wu

ACI 376-11

Consulting members Robert Arvedlund James P. Lewis Terry Turpin

СНА	PTER 2—NOTATION AND DEFINITIONS	.7	,
2.1	Notation	7	1

2.1-	-Notation	• •	•	•	 •	•	٠	•	•	٠	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	٠	•	•	• •	. /	
2.2-	-Definitions		•	•				•	•	•		•		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•		8	

#### CHAPTER 3—REFERENCED STANDARDS .....14

CHAPTER 4—MATERIALS
4.1—Testing of materials
4.2—Cementitious materials
4.3—Aggregates
4.4—Water
4.5—Admixtures
4.6—Fibers
4.7—Deformed reinforcement
4.8—Plate steel composite with concrete
4.9—Prestressed reinforcement
4.10—Prestressing anchorages
4.11—Post-tensioning ducts
4.12—Grout
4.13—Metal liners and nonstructural metal components .22
4.14—Insulation
4.15—Coating requirements

ACI 376-11 was adopted November 11, 2011, and was published May 2013. Copyright © 2013, American Concrete Institute.

All rights reserved including rights of reproduction and use in any form or by any means, including the making of copies by any photo process, or by electronic or mechanical device, printed, written, or oral, or recording for sound or visual reproduction or for use in any knowledge or retrieval system or device, unless permission in

<b>CHAPTER 5—DESIGN</b>	LO	AC	)S.	 	 		 /	24
5.1—Design loads				 	 	 	 	.24
5.2—Loading conditions.				 	 	 	 	.28

#### **CHAPTER 6—MINIMUM PERFORMANCE**

REQUIREMENTS	.31
6.1—General	31
6.2—Primary concrete container	31
6.3—Secondary concrete container	34
6.4—Roof performance criteria	35
6.5—Other performance criteria	35
6.6—Concrete quality	36
6.7—Shotcrete	40
6.8—Coating design	40
6.9—Metal components	41

CHAPTER	7—LOAD	FACTORS	 	.42
••••••••••••••••••••••••••••••••••••••			 	

7.1—General
7.2—Load factors for ultimate limit state of primary
container
7.3—Load factors for ultimate limit state of secondary
container

CHAPTER 8—ANALYSIS AND DESIGN	49
8 1—Methods of analysis	49

• •	• •	• •	•	• •	• •	٠	• •	•	٠	• •	•	٠	• •	•	49	
			•												54	
			•												54	
			•												55	
			•	•••		•			•	• •	•	•	• •	• •	58	
	· · · · · · ·	· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·	· · · · · · · · · · · · · · · · · · ·					· · · · · · · · · · · · · · · · · · ·			· · · · · · · · · · · · · · · · · · ·		· · · · · · · · · · · · · · · · · · ·	

CHAPTER 9—DETAILII	NG	 60

9.1—General	.60
9.2—Reinforcement details	.60
9.3—Internal prestressing systems	.61
9.4—External prestressing systems	.63
9.5—Concrete containment wall	.63
9.6—Metal components	.65
9.7—Anchorage to concrete	.66
9.8—Liners and coatings	.67

#### CHAPTER 10—FOUNDATIONS ......69

10.1—General	69
10.2—Geotechnical investigation	69
10.3—Design requirements for shallow foundations	72
10.4—Design requirements for deep foundations	76
10.5—Ground improvement	80
10.6—Foundation details	80
10.7—Foundation performance monitoring details	
10.8—Monitoring frequency	84
10.9—Inspection and testing	85

### CHAPTER 11—CONSTRUCTION

REQUIREMENTS	87
11.1—Construction plan	87
11.2—Tolerances	87

11.3—Shotcrete for external prestressing systems90
11.4—Post-tensioning
11.5—Winding of prestressed reinforcement: wire or
strand
11.6—Forming
11.7—Construction joints
11.8—Concrete embedments
11.9—Coatings
11.10—Welding

## CHAPTER 12—COMMISSIONING/

DECOMMISSIONING99
12.1—Scope
12.2—Testing
12.3—Pressure and vacuum testing104
12.4—Purging into service
12.5—Cool-down
12.6—Settlement and movement monitoring108
12.7—Liquefied natural gas tank fill methods
12.8—Decommissioning: purging out of service and
warm-up
12.9—Recordkeeping111
12.10—Nameplate

## APPENDIX A-TANK CONFIGURATIONS, DETAILS,

AND EXAMPLES	. 113
RA.1—Tank configurations	113
RA.2—Full-containment tanks: typical details	113
RA.3—Examples of base joint details	113

# APPENDIX B—OFFSHORE CONCRETE

TERMINALS124
B.1—Scope
B.2—General
B.3—Loads and load combinations
B.4—Concrete and reinforcement materials
B.5—Global and local structural analysis
B.6—Criteria and methodology of concrete sectional
design
B.7—Fatigue performance criteria
B.8—Design considerations during construction,
transportation, and installation
B.9—Decommissioning
B.10—Design for accidents
APPENDIX C—FATIGUE PERFORMANCE 139
C.1—Scope
C.2—General
C.3—Fatigue performance criteria
COMMENTARY REFERENCES142

#### INTRODUCTION

ACI Committee 376 was formed and subsequently ACI 376-11 was drafted in response to a request from the National Fire Protection Association (NFPA) Technical Committee 59A on liquefied natural gas (LNG). That committee is responsible for NFPA 59A, which is an internationally recognized standard governing the production, storage, and handling of LNG at an operating temperature of  $-270^{\circ}$ F.

NFPA 59A contains provisions for the use of reinforced concrete and prestressed concrete for two principal applications: 1) impoundment—secondary containment in conjunction with a metallic primary container; and 2) storage—primary containment. NFPA 59A is somewhat limited; it does not provide guidelines specifically tailored to concrete use at cryogenic temperatures. This limitation was the impetus for Committee 59A's request. Although the request was related specifically to containment of LNG, this code addresses concrete use for other refrigerated liquefied gas (RLG) as well, ranging in operating temperatures from +40 to  $-325^{\circ}$ F. This makes the code and commentary analogous to the American Petroleum Institute's API 620, which governs design and construction of steel and aluminum RLG storage tanks to  $-270^{\circ}$ F.

The most common use of reinforced concrete and prestressed concrete in cryogenic storage applications is for secondary containment around metal primary storage tanks. Prestressed concrete primary containment tanks were built in North America and Europe from the 1960s through the 1980s. Renewed interest in the use of concrete for primary containment and the need for a code that addressed secondary concrete containment led to the development of this code, which includes pertinent excerpts from ACI 318-11 and ACI 350-06. The commentary includes considerations by the committee in developing the code.

The commentary is not intended to provide a complete historical background concerning development of the code, nor is it intended to provide a detailed summary of the studies and research data reviewed by the committee in formulating its provisions. References to specific research data are provided for more in-depth study of the background materials.

ACI 376 may be used as a part of a legally adopted code and, as such, must differ in form and substance from documents that provide detailed specifications, recommended practice, complete design procedures, or design aids.

Requirements more stringent than the code provisions are desirable for unusual structures. This code and commentary cannot replace sound engineering knowledge, experience, and judgment. A code for design and construction states the minimum requirements necessary to provide for public health and safety. ACI 376 is based on this principle. For any structure, the owner and engineer may require the quality of materials and construction to be higher than the minimum requirements necessary to provide serviceability and to protect the public as stated in the code. Lower standards, however, are not permitted.

ACI 376 has no legal status unless it is adopted by regulatory bodies. Where the code has not been adopted, it may serve as a reference to good practice. The code provides a means of establishing minimum standards for acceptance of design and construction by a legally appointed official or designated representative. The code and commentary are not intended for use in settling disputes between the owner, engineer, contractor, or their agents, subcontractors, material suppliers, or testing agencies. Therefore, the code cannot define the contract responsibility of each of the parties in typical construction. General references requiring compliance with ACI 376 in the job specifications should be avoided because the contractor is rarely in a position to accept responsibility for design details or construction requirements that depend on a detailed knowledge of the design. Generally, the contract documents should contain all of the necessary requirements to ensure compliance with the code. In part, this can be accomplished by reference to specific code sections in the job specifications. Other ACI publications, such as ACI 301, are written specifically for use as contract documents for construction.

#### CHAPTER 1-GENERAL

#### 1.1—Scope

This code provides minimum requirements for design and construction of reinforced concrete and prestressed concrete structures for the storage and containment of refrigerated liquefied gases (RLG) with service temperatures between +40 and  $-325^{\circ}$ F. Notwithstanding, the principals listed herein are applicable to concrete foundations of double-steel tanks subject to the approval of the owner.

Container design shall include the design of the container wall, its foundation (footing and floor slab), the concrete portions of its roof, and the bund wall, whenever applicable.

#### R1.1—Scope

Typically, reinforced concrete and prestresssed concrete structures for the containment of RLGs are classified into two main categories:

COMMENTARY

a) Secondary containment, which represents the most widespread use of such structures

b) Primary containment

Henceforth in this document, the term "concrete" is used to denote both conventionally reinforced and prestressed concrete. This code is not applicable to the design of membrane tanks because construction and detailing requirements are not included. A membrane tank has a non-selfsupporting thin layer (membrane) inner tank that is supported through insulation by an outer tank. With appropriate additional engineering analysis and justification, portions of this code may be applied to the design of a concrete outer tank of a membrane tank using both primary and secondary tank criteria. This code does not address the materials, design, or construction of steel primary or secondary tanks. Such information is further described in API 620.

This code has been developed with the lowest operating temperature of  $-325^{\circ}$ F. Lower product temperatures could also be used, however, provided appropriate additional engineering analysis and justification is performed for each proposed application. Single containment, double containment, and full containment concepts are covered by this code.

A concrete bund wall is an open-top cylindrical wall serving as the outer boundary of an impounding area surrounding a single-containment RLG storage tank.

In a double-containment tank system, the primary container is normally a single-containment RLG storage tank with a vapor-tight shell and roof designed to contain both refrigerated liquid and the associated vapors under normal operating conditions. In this system, the secondary container is often an open-top concrete wall that serves two basic functions:

a) Provides protection to the primary container from external loads under normal operating conditions

b) Contains the leakage from the primary container (but not the vapor generated from such leakage) under accidental-spill conditions

In a full-containment tank system, the primary container is designed to contain the refrigerated liquid under normal operating conditions. In this system, the secondary container is a vapor-tight wall with a vapor-tight roof that spans over the inner tank. The roof may be metal, concrete, or a composite of the two materials.

Under normal operating conditions, the secondary container provides protection to the primary container from external loads. Under accidental-spill conditions, the secondary container also contains the leakage from the primary container and contains or controls the vapor generated from such leakage.

#### COMMENTARY

Only material selection criteria are included for the thermal corner protection (TCP) of a secondary tank in this code. The design parameters, analysis methods, acceptance criteria (stress or strain limits), and detailing and construction requirements for TCP are excluded from this code.

#### 1.2—Quality assurance

**1.2.1** *Plan*—The project specifications shall include provisions for developing a quality assurance plan to verify that materials, fabrication, and construction conform to the design. The plan shall include:

1. Procedures for exercising control of fabrication and construction;

2. Required inspections and tests; and

3. Inspection and test procedures.

**1.2.2** *Traceability*—The location of all permanent materials in the structure shall be traceable to source documents demonstrating compliance with specifications, standards, tests, and quality assurance and quality control requirements. The quality assurance/quality control system documents shall identify which component or material in the structure was tested or certified.

#### 1.2.3 Documentation

**1.2.3.1** Documentation of materials, testing, and performance measurements and results shall be provided in a quality assurance/quality control system specified in the project specifications.

**1.2.3.2** The quality assurance/quality control system documents shall be adequately detailed to identify precisely which component or material in the structure was tested. Records of all test results shall be preserved and disposition of failed materials documented.

**1.2.3.3** Documentation of all materials, testing, and performance measurements and results shall be available at all times during construction.

#### R1.2—Quality assurance

**R1.2.1** For the design-build approach typically used for RLG tank construction, the project specifications will provide only an outline of the quality assurance requirements. The design-build contractor is typically responsible for developing details of the quality assurance plan and quality control.

R1.2.2 Source documents should include:

1. Mill certificates demonstrating conformity with ASTM or other applicable standards for metal and concrete and grout components;

2. Certification of conformance to standards and specifications from material suppliers;

3. Truck batch tickets for ready mixed concrete, and results of field and laboratory tests for concrete and grout placed at the site;

4. Weld procedure specifications used for welding of reinforcement, plate, and structural steel; and

5. Qualifications of welders, shotcrete nozzlemen, and inspectors or other personnel performing tests and inspections.

**R1.2.3.1** All certifications, quality assurance/quality control records, design drawings, specifications, and construction records of any kind should be assembled by the owner in a logical manner that facilitates later recovery and review. All documentation should be furnished in paper and electronic formats. The owner should maintain these documents through the life of the tank.

#### COMMENTARY

#### CHAPTER 2-NOTATION AND DEFINITIONS

#### 2.1—Notation

- B = blast (Chapters 5, 7)
- c = specific heat (Chapter 6)
- C = experimentally determined fatigue coefficient (Appendix C)
- C = penetration coefficient (Chapter 8)
- D =tank diameter (Chapter 10)
- D = dead loads, or related internal moments and forces (Chapters 5, 7)
- $D_p$  = projectile diameter (Chapter 8)
- E = environmental load (Chapter 7)
- $E_c$  = modulus of elasticity of concrete (Chapters 2, 6)
- $E_o$  = operating basis earthquake (Chapters 2-8, 10, Appendix B)
- $E_s$  = safe shutdown earthquake product (service) (Chapter 5)
- $f_{c'}$  = specified compressive strength of concrete (Chapters 6, 8, Appendix C)
- $f_{ci'}$  = specified compressive strength of concrete at time of initial prestress (Chapters 2, 5-8, 10, Appendix B)
- F = loads due to weight and pressure of fluids with well-defined densities and controllable maximum heights, or related internal moments and forces (Chapters 5, 7)
- $F_s$  = foundation settlement (Chapter 5)
- $F_t$  = maximum hydrostatic load due to test water (Chapter 5)
- $F_v$  = vertical earth pressure (Chapter 5)
- g = gravitational constant
- $h_d$  = minimum dome thickness to resist buckling (Chapter 6, 8)
- H = heat radiation from adjacent fire
- $k = \text{different stress magnitudes in a spectrum, } S_i (1 \le i \le k) (\text{Appendix C})$
- k = intrinsic coefficient of permeability (Chapter 5-7)
- K = coefficient of hydraulic conductivity (Chapter 6)
- L = live load (primarily snow; also: temporary equipment, roof live load) (Chapters 5, 7)
- $L_{cm}$  = live load effects resulting from commissioning activities (Chapter 7)
- $L_{cn}$  = live load effects resulting from construction activities (Chapter 7)
- $m_p$  = projectile mass, lb (Chapter 8)
- $M_i$  = missile impact (Chapters 5, 7)
- $n(S_i) =$  contributing stress cycle
- $N_i(S_i)$  = number of cycles to failure of a constant stress reversal,  $S_i$  (Appendix C)
- $P_d$  = internal pressure (service) (Chapter 5)
- $P_e$  = accidental internal overpressure (applies to fullcontainment outer wall and domed roof) (Chapter 5)
- $P_f$  = final prestressing (at service load) (Chapters 5, 7)
- $P_i$  = initial prestressing (at transfer) (Chapters 5, 7)
- $P_t$  = internal pressure (test) (Chapter 5)

#### COMMENTARY

- $P_u$  = factored axial force; to be taken as positive for compression and negative for tension (Chapter 8)
- $P_{\nu}$  = accidental vacuum pressure (applies to full-containment outer wall only) (Chapter 5)
- r = tank radius (Chapter 11)
- $r_d$  = nominal radius of curvature of dome (Chapter 11)
- $r_{imp}$  = average radius of curvature of dome in an imperfection region (Chapter 5, 8)
- R = roof loads (appurtenances and suspended ceiling)(Chapter 5)
- R =force reduction factor (Chapter 8)
- R = earthquake response component (Appendix B)
- $S_i$  = constant stress reversal (Appendix C)
- T = cumulative effect of temperature, creep, shrinkage, and differential settlement (Chapters 5, 7)
- $T_c$  = loads associated with the creep of concrete (Chapter 7)
- $T_{ds}$  = loads associated with differential settlement (Chapter 7)
- $T_e$  = temperature and temperature differential due to sudden cooling (Chapters 5, 7)
- $T_o$  = temperature and temperature differential at service loads (Chapter 5)
- $T_o$  = internal moments and forces caused by temperature and moisture distributions within concrete structure as a result of commissioning, normal operating, or decommissioning conditions (Chapter 7)
- $T_s$  = loads associated with shrinkage of concrete (Chapter 7)
- v =projectile speed (Chapter 8)
- w = concrete density (Chapter 8)
- W =wind (Chapters 5, 7)
- $q_u$  = ultimate bearing capacity (Chapter 10)
- $Q_a$  = pile safe design load (Chapters 2, 10)
- $Q_r$  = ultimate capacity of single piles (Chapter 10)
- $\beta_c$  = buckling strength reduction factor due to creep, material nonlinearity, and cracking of concrete (Chapter 8)
- $\beta_{imp}$  = buckling strength reduction factor due to imperfections (Chapter 8)
- $\phi$  = strength reduction factor (Chapters 7, 8)
- $\mu$  = Poisson's ratio, or dynamic viscosity of fluid (Chapter 6)
- $\rho$  = density of fluid (Chapter 6)

#### 2.2-Definitions

For consistent application of this code, it is necessary that terms be defined where they have particular meanings in this code. The definitions given are for use in application of this code only and do not always correspond to ordinary usage. A glossary of most-used terms relating to cement manufacturing, concrete design and construction, and research in concrete is contained in "Concrete Terminology," available on the ACI Web site.

**abnormal load**—load that arises from an uncontrolled or unplanned situation with safety or environmental consequences.