

ACI 549.5R-16

Report on Spray-Up and Continuous Strand Glass Fiber-Reinforced Concrete (GFRC)

Reported by ACI Committee 549



American Concrete Institute
Always advancing

This is a preview. [Click here to purchase the full publication.](#)



Report on Spray-Up and Continuous Strand Glass Fiber-Reinforced Concrete (GFRC)

Copyright by the American Concrete Institute, Farmington Hills, MI. All rights reserved. This material may not be reproduced or copied, in whole or part, in any printed, mechanical, electronic, film, or other distribution and storage media, without the written consent of ACI.

The technical committees responsible for ACI committee reports and standards strive to avoid ambiguities, omissions, and errors in these documents. In spite of these efforts, the users of ACI documents occasionally find information or requirements that may be subject to more than one interpretation or may be incomplete or incorrect. Users who have suggestions for the improvement of ACI documents are requested to contact ACI via the errata website at <http://concrete.org/Publications/DocumentErrata.aspx>. Proper use of this document includes periodically checking for errata for the most up-to-date revisions.

ACI committee documents are intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. Individuals who use this publication in any way assume all risk and accept total responsibility for the application and use of this information.

All information in this publication is provided “as is” without warranty of any kind, either express or implied, including but not limited to, the implied warranties of merchantability, fitness for a particular purpose or non-infringement.

ACI and its members disclaim liability for damages of any kind, including any special, indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use of this publication.

It is the responsibility of the user of this document to establish health and safety practices appropriate to the specific circumstances involved with its use. ACI does not make any representations with regard to health and safety issues and the use of this document. The user must determine the applicability of all regulatory limitations before applying the document and must comply with all applicable laws and regulations, including but not limited to, United States Occupational Safety and Health Administration (OSHA) health and safety standards.

Participation by governmental representatives in the work of the American Concrete Institute and in the development of Institute standards does not constitute governmental endorsement of ACI or the standards that it develops.

Order information: ACI documents are available in print, by download, on CD-ROM, through electronic subscription, or reprint and may be obtained by contacting ACI.

Most ACI standards and committee reports are gathered together in the annually revised ACI Manual of Concrete Practice (MCP).

American Concrete Institute
38800 Country Club Drive
Farmington Hills, MI 48331
Phone: +1.248.848.3700
Fax: +1.248.848.3701

www.concrete.org

Report on Spray-up and Continuous Strand Glass Fiber-Reinforced Concrete (GFRC)

Reported by ACI Committee 549

John Jones*, Chair

Corina-Maria Aldea[†]
P. N. Balaguru
Hiram Price Ball Jr.[†]
Nemkumar Banthia
Gordon B. Batson
Neeraj J. Buch
Cesar Chan
James I. Daniel
Antonio De Luca
Ashish Dubey[†]

Garth J. Fallis
Graham T. Gilbert[†]
Antonio J. Guerra
James R. McConaghy
Barzin Mobasher[†]
Antoine E. Naaman
Antonio Nanni[†]
James E. Patterson[†]
Alva Peled
Martin Pullan

D. V. Reddy
Larry Rowland[†]
Paul T. Sarnstrom
Scott Shafer[†]
Surendra P. Shah
Yixin Shao
Robert C. Zellers

Consulting Members
Lloyd E. Hackman

Paul Nedwell
P. Paramasivam
Parviz Soroushian
Ronald F. Zollo

*Chair of subcommittee responsible for preparing this report.

[†]Members of subcommittee that prepared this report.

The committee thanks P. H. Mokhiber for his contributions.

Glass fiber-reinforced concrete (GFRC) is a popular construction material used to manufacture precast concrete products in architectural and civil engineering applications. GFRC products have desirable aesthetics and physical properties, including durability, strength, toughness, moisture resistance, dimensional stability, and fire resistance. This report summarizes the processes, properties, and applications of GFRC made by the spray-up process, and processes that use continuous strands and woven, knitted, or bonded textiles.

Keywords: alkali-resistant glass fiber; architectural panels; cement boards; composites; concrete panels; ductility; durability; fiber-reinforced concrete; filament winding; formwork; glass fiber-reinforced concrete; glass-reinforced concrete; mesh reinforcement; permanent formwork; premix; precast concrete; spray-up process; textile-reinforced concrete; toughness.

CONTENTS

CHAPTER 1—INTRODUCTION AND SCOPE, p. 2

1.1—Introduction, p. 2

ACI Committee Reports, Guides, and Commentaries are intended for guidance in planning, designing, executing, and inspecting construction. This document is intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. The American Concrete Institute disclaims any and all responsibility for the stated principles. The Institute shall not be liable for any loss or damage arising therefrom.

Reference to this document shall not be made in contract documents. If items found in this document are desired by the Architect/Engineer to be a part of the contract documents, they shall be restated in mandatory language for incorporation by the Architect/Engineer.

1.2—History, p. 2

1.3—Scope, p. 3

CHAPTER 2—NOTATION AND DEFINITIONS, p. 3

2.1—Notation, p. 3

2.2—Definitions, p. 3

CHAPTER 3—APPLICATIONS, p. 4

3.1—Glass fiber-reinforced concrete architectural cladding, p. 4

3.2—Textile-reinforced concrete, p. 9

3.3—Glass fiber-reinforced concrete filament-wound poles, p. 10

3.4—GFRC permanent formwork, p. 12

3.5—Flat and profiled panel products, p. 14

CHAPTER 4—FABRICATION, p. 15

4.1—Spray-up process, p. 15

4.2—Textile-reinforced concrete, p. 17

4.3—Filament winding, p. 17

CHAPTER 5—PROPERTIES, p. 18

5.1—General properties, p. 18

5.2—Fire properties, p. 20

5.3—Long-term properties, p. 20

5.4—Freezing-and-thawing resistance, p. 21

ACI 549.5R-16 was adopted and published March 2016.

Copyright © 2016, American Concrete Institute.

All rights reserved including rights of reproduction and use in any form or by any means, including the making of copies by any photo process, or by electronic or mechanical device, printed, written, or oral, or recording for sound or visual reproduction or for use in any knowledge or retrieval system or device, unless permission in writing is granted by the American Concrete Institute.

- 5.5—Creep, p. 21
5.6—Sustainability, p. 21

CHAPTER 6—DESIGN PROCEDURES, p. 22

- 6.1—U.S. glass fiber-reinforced concrete design practice, p. 22
6.2—European glass-reinforced concrete design practice, p. 23
6.3—Recently proposed design procedure, p. 23

CHAPTER 7—REFERENCES, p. 26

- Authored documents, p. 26

CHAPTER 1—INTRODUCTION AND SCOPE

1.1—Introduction

Glass fiber-reinforced concrete (GFRP) is a composite of alkali-resistant (AR) glass fibers embedded in a cementitious mixture, which could be a paste, mortar, or concrete, possibly with additives and admixtures added for improved processability, properties, or both. The fibers could be short individual fibers or monofilaments; bundles of fibers, which are often referred to as chopped strands; continuous strands or roving, or textiles (Fig. 1.1). Textiles are also synonymously called scrims, fabrics, or meshes.

Only AR glass fibers should be used in GFRP composites, to which this report is confined. There are four processes used to manufacture GFRP:

- 1) Premix
- 2) Spray-up, which usually contains a minimum of 4 percent chopped AR glass fiber roving strands by mass of the composite traditionally referred to as GFRP
- 3) Textile-reinforced concrete (TRC), which uses continuous structured AR glass fibers in woven (typically leno weave), knitted, and bonded constructions such as fabrics, scrims, or meshes
- 4) Continuous strands in oriented patterns such as filament winding

This report covers Items 2 through 4 and is a companion to **ACI 549.3R**, which covers Item 1.

GFRP is not just a single material, but rather a variety of materials with different properties and performance characteristics. Because GFRP in any of its forms does not contain steel reinforcing bars, there is no need of extra concrete cover to protect steel against corrosion. This allows it to be produced in thin sections, typically 0.5 to 1.0 in. (13 to 25 mm), which makes GFRP products much lighter in weight compared to conventional concrete products, which are usually 2 in. (50 mm) or thicker, although both are similar in density.

GFRP products have several significant advantages over conventional precast concrete products. They are lightweight, easy to handle and install, and have high toughness. Being lightweight offers cost-effective concrete-based alternatives in applications where the heavy weight of conventional precast concrete would make it unsuitable.

Research on GFRP composites began in the 1960s and has been in successful commercial use for over 40 years. This is proof that, if designed and manufactured to accepted recom-



Fig. 1.1—Alkali-resistant glass fiber roving, chopped strands, and textile (bonded scrim).

Table 1.2a—Chemical composition of selected glasses, percent of total by mass

Component	A-glass	E-glass	AR glass #1	AR glass #2
SiO ₂	73.0	54.0	62.0	61.0
Na ₂ O	13.0	—	14.8	15.0
CaO	8.0	22.0	—	—
MgO	4.0	0.5	—	—
K ₂ O	0.5	0.8	—	2.0
Al ₂ O ₃	1.0	15.0	0.8	—
Fe ₂ O ₃	7.0	0.3	—	—
B ₂ O ₃	—	7.0	—	—
ZrO ₂	—	—	16.7	17.5
TiO ₂	—	—	1.0	—
Li ₂ O	—	—	—	1.0

mended practices, GFRP has a durability and longevity to be an acceptable building material. Its properties have been thoroughly researched, probably as much as, if not more than, any other material. Further research and development of new applications and mass production processes will move GFRP into the next phase of large-scale use.

1.2—History

Much of the original research performed on glass fiber-reinforced cement paste took place in the early 1960s. This work used conventional borosilicate glass fibers (E-glass) and soda-lime-silica glass fibers (A-glass). The chemical compositions, densities, and mechanical properties of E- and A-glass are listed in Tables 1.2a and 1.2b. Glass compositions of E- and A-glass were found to lose strength quickly because of the high alkalinity (pH \geq 12.5) of portland cement-based materials. Consequently, early A- and E-glass cementitious composites were unsuitable for long-term use (Larner et al. 1976). Some E-glass products have been developed with alkali-resistant (AR) coatings, but