

Steel Design Guide Series

## Low-and Medium-Rise Steel Buildings



This is a preview. Click here to purchase the full publication.





# Low- and Medium-Rise Steel Buildings

**Design Guide for Low- and Medium-Rise Steel Buildings** 

Horatio Allison, PE Consulting Engineer Dagsboro, Delaware Copyright © 1991

by

American Institute of Steel Construction, Inc.

#### All rights reserved. This book or any part thereof must not be reproduced in any form without the written permission of the publisher.

The information presented in this publication has been prepared in accordance with recognized engineering principles and is for general information only. While it is believed to be accurate, this information should not be used or relied upon for any specific application without competent professional examination and verification of its accuracy, suitability, and applicability by a licensed professional engineer, designer, or architect. The publication of the material contained herein is not intended as a representation or warranty on the part of the American Institute of Steel Construction or of any other person named herein, that this information is suitable for any general or particular use or of freedom from infringement of any patent or patents. Anyone making use of this information assumes all liability arising from such use.

Caution must be exercised when relying upon other specifications and codes developed by other bodies and incorporated by reference herein since such material may be modified or amended from time to time subsequent to the printing of this edition. The Institute bears no responsibility for such material other than to refer to it and incorporate it by reference at the time of the initial publication of this edition.

Printed in the United States of America

Second Printing: October 2003

This is a preview. Click here to purchase the full publication.

## TABLE OF CONTENTS

BASIC DESIGN RULES FOR ECONOMY	1
LIVE LOAD AND BAY SIZE SELECTION Live Load Selection Bay Size Selection	1 2 2
COMPOSITE FLOORS	5
Allowable Stress (ASD) and Load	
Resistance Factor Design (LRFD)	5
Economy with LRFD	6
Floor Load Capacity Enhancement	6
Shored vs. Unshored Construction	7
Serviceability Considerations	8
Underfloor Duct Systems	8
OPEN WEB JOIST FLOOR SYSTEMS	10
Joist Size and Spacing	10

Girder Beam Design	10
Composite Joist Systems	10
Floor Vibration	11
WIND LOAD DESIGN	12
Drift Limits	12
"K" Bracing Frame	13
Unbraced Frame Design	15
Special Wind Frames	17
APPENDICES	23
LRFD Composite Beam Design	23
Composite Beam Load Capacity Enhancement	25
Composite Beam Long Term Deflection	29
Steel Joist Typical Bay	31
K-Frame Bracing Optimization	33
Unbraced Frame Design	36

iii

This is a preview. Click here to purchase the full publication.

## PREFACE

This booklet was prepared under the direction of the Committee on Research of the American Institute of Steel Construction, Inc. as part of a series of publications on special topics related to fabricated structural steel. Its purpose is to serve as a supplemental reference to the AISC Manual of Steel Construction to assist practicing engineers engaged in building design.

The design guidelines suggested by the author that are outside the scope of the AISC Specifications or Code do not represent an official position of the Institute and are not intended to exclude other design methods and procedures. It is recognized that the design of structures is within the scope of expertise of a competent licensed structural engineer, architect, or other licensed professional for the application of principles to a particular structure.

The sponsorship of this publication by the American Iron and Steel Institute is gratefully acknowledged.

The information presented in this publication has been prepared in accordance with recognized engineering principles and is for general information only. While it is believed to be accurate, this information should not be used or relied upon for any specific application without competent professional examination and verification of its accuracy, suitability, and applicability by a licensed professional engineer, designer, or architect. The publication of the material contained herein is not intended as a representation or warranty on the part of the American Institute of Steel Construction, Inc. or the American Iron and Steel Institute, or of any other person named herein, that this information is suitable for any general or particular use or of freedom from infringement of any patent or patents. Anyone making use of this information assumes all liability arising from such use.

### **DESIGN OF LOW- AND MEDIUM-RISE STEEL BUILDINGS**

#### BASIC DESIGN RULES FOR ECONOMY

A few basic design rules for economy will be presented herein. These rules should be considered in the conceptual phase in the design of a project. There are, of course, many other considerations, but these suggestions are simple and can help in producing a good economical design.

The cost of a filler beam and/or girder beam simply consists of the cost of the mill material, the cost of fabrication, and the cost of erection. The cost of fabrication and erection for a single beam is essentially the same for a heavy beam or a light beam. The real savings for a light member compared to a heavier one is simply the difference in the cost of the mill material. Thus, beams should be spaced as far apart as practical to reduce the number of pieces which must be fabricated and erected.

Rigid moment connections and special connections for bracing are expensive. Care should be taken to minimize the number of these types of connections in a project—that is, reduce the number of moment resisting and braced bents to the minimum. Where practical, one may consider the use of only spandrel moment resisting frames to resist wind loads. Deeper, more efficient sections may be used thus minimizing the number of moment resisting connections required.

Where appropriate, high strength steel ( $F_y = 50$  ksi) should be used in lieu of mild steel ( $F_v = 36$  ksi) for both columns and beams. The reason is simple-the price to strength ratio is about 25% lower for the higher strength steel beams and 10% to 15% lower for columns depending upon their length. For example, a W21x44 ( $F_y = 36$  ksi) simple filler beam is the equivalent of a W16x26 ( $F_v = 50$  ksi) composite filler beam. The difference in the cost of the mill material to the fabricator is about \$3.90 per linear foot. The cost of the studs in place at a cost of \$1.50 each is about \$1.30 per linear foot. The cost of cambering or shoring is considerably less than the \$2.60 per foot difference. The floor vibration ratings for the two beams are comparable. The required critical damping using Murray's criterion (Murray, 1991) for the W21x44 and W16x26 spanning 30'-0" spaced 10'-0" o.c. with 10 psf ambient live load is 4.00 and 3.46 respectively. The higher strength steel beam is less costly and functionally equivalent. It should be kept in mind that there are situations where the use of high strength steel is inappropriate. Small inconsequential filler beams, channels, angles, etc., should be of  $F_y = 36$  ksi steel, as this material is readily available from a fabricator's stock or a steel supply warehouse. Members for which strength is not the controlling design consideration, obviously  $F_v = 36$  ksi material should be used.

Repetitive use of members and/or the same shape size is an important factor in the design of an economical project. Repetitive use of members reduces the detailing, fabrication, and erection costs. As an example, in composite construction where beam spacing for non-typical areas is reduced, consideration should be given to the use of the typical size beam section with a reduction in the number of studs. The simpler the framing, the lower the final estimated cost is likely to be at bid time and, as a result, the lower the total square foot cost of the project.

Use live load reductions for the design of members where possible. While live load reduction may not result in any substantial reduction in filler beam weights, a change of one size, perhaps a reduction from a W16x31 to a W16x26, will result in a 16% savings in the filler beam mill material required. The savings in girder and column weights and the cost of foundations are likely to be significant.

The level of inspection specified should be consistent with that required to insure that the completed structure will be functional. Except in unusual circumstances, visual inspection should be adequate for fillet welds. The extent of nondestructive testing of butt welds may be finally determined during the construction period. If the results of tests are marginal, the number of tests can be increased. If the results of the tests are consistently good, the number of tests may be reduced. Especially for large projects, it may be prudent to require AISC certified fabricators in order to insure good quality control and a more trouble-free project.

Finally, paint only members required by the AISC Specification. Unpainted surfaces should be used when in contact with concrete. Fireproofing material more readily adheres to unpainted surfaces. While painting costs may only be \$.15 to \$.20 per square foot, for a 200,000 square foot project the cost saving of \$30,000 to \$40,000 is real and is there for the taking.

#### LIVE LOAD AND BAY SIZE SELECTION

Most buildings are economic machines of one sort or another. In particular, many office building structures are built on a speculative basis. The success of the venture may be a function of the building's planning and serviceability potential. Larger bay sizes increase the flexibility in space planning. Higher design live loads also increase the flexibility in the uses permitted in office space. Buildings with higher live load capacities and larger bay sizes are obviously more attractive to potential building tenants and more valuable to building owners. It will be shown that larger bay sizes and higher