

Australian Standard<sup>®</sup>

## Vehicle loop detector sensors



This Australian Standard® was prepared by Committee LG-006, Road Traffic Signals. It was approved on behalf of the Council of Standards Australia on 13 November 2008. This Standard was published on 17 December 2008.

---

The following are represented on Committee LG-006:

- ARRB Transport Research Limited
  - Australian Industry Group
  - AUSTROADS
  - Brisbane City Council
  - Department for Transport, Energy and Infrastructure (SA)
  - Hire and Rental Industry Association of Australia
  - IES: The Lighting Society
  - Lighting Council of Australia
  - Main Roads Department, Qld
  - Roads and Traffic Authority of NSW
  - VicRoads
- 

This Standard was issued in draft form for comment as DR 07371.

Standards Australia wishes to acknowledge the participation of the expert individuals that contributed to the development of this Standard through their representation on the Committee and through the public comment period.

---

### **Keeping Standards up-to-date**

Australian Standards® are living documents that reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued.

Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments that may have been published since the Standard was published.

Detailed information about Australian Standards, drafts, amendments and new projects can be found by visiting **[www.standards.org.au](http://www.standards.org.au)**

Standards Australia welcomes suggestions for improvements, and encourages readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at **[mail@standards.org.au](mailto:mail@standards.org.au)**, or write to Standards Australia, GPO Box 476, Sydney, NSW 2001.

---

Australian Standard<sup>®</sup>

## Vehicle loop detector sensors

Originated as AS 2703—1984.  
Previous edition 1987.  
Third edition 2008.

### **COPYRIGHT**

© Standards Australia

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia GPO Box 476, Sydney, NSW 2001, Australia

ISBN 0 7337 8984 6

## PREFACE

This Standard was prepared by Standards Australia Committee LG-006, Road Traffic Signals, to supersede AS 2703—1987. It is one of the following group of Standards, which set out requirements for equipment associated with traffic signal installations:

### AS

- 2339 Traffic signal posts and attachments
- 2353 Pedestrian push-button assemblies
- 2578 Traffic signal controllers
- 2578.1 Part 1: Physical and electrical compatibility
- 2703 Vehicle loop detector sensors (this Standard)
- 2979 Traffic signal mast arms
- 4113 Traffic signal lamps
- 4113.1 Part 1: Lamps for 240 V a.c. operation
- 4113.2 Part 2: Lamps for a.c. operation at extra-low voltage
- 4191 Portable traffic signal systems
- 4192 Illuminated flashing arrow signs

### AS/NZS

- 2144 Traffic signal lanterns

This Standard applies particularly to the electronic equipment used in traffic control and counting systems for the detection of vehicles. Such equipment is used in conjunction with inductive wire loops buried beneath the surface of the road pavement to provide the detection system. To a major extent the detection characteristics are determined by the actual loop configuration used. Standards for the cables used in the construction of these loops are as follows:

### AS/NZS

- 2276 Cables for traffic signal installations
- 2276.2 Part 2: Feeder cable for vehicle detectors
- 2276.3 Part 3: Loop cable for vehicle detectors

The requirements of Section 4 of this Standard have been framed in such a way that the performance of vehicle loop detector sensors can be assessed independently of other elements of the detection system. A suggested series of type tests for checking the operational performance of the sensors is provided in Appendix B. Recommended routine tests are described in Appendix C.

The major changes to this edition of the Standard relate to the addition of integral detector units, which are sensor units incorporated integrally within a traffic signal controller. Also, the size restriction for independent multi-channel detector units has been reduced significantly. Other changes involve corrections of existing requirements or editorial clarifications.

The terms ‘normative’ and ‘informative’ have been used in this Standard to define the application of the appendix to which they apply. A ‘normative’ appendix is an integral part of a Standard, whereas an ‘informative’ appendix is only for information and guidance.

## CONTENTS

	<i>Page</i>
<b>SECTION 1 SCOPE AND GENERAL</b>	
1.1 SCOPE .....	5
1.2 REFERENCED DOCUMENTS .....	5
1.3 DEFINITIONS .....	6
<b>SECTION 2 MECHANICAL AND PHYSICAL REQUIREMENTS</b>	
2.1 CONSTRUCTION.....	9
2.2 OVERALL DIMENSIONS.....	9
2.3 MARKING .....	9
2.4 PROVISION OF INFORMATION.....	9
<b>SECTION 3 ELECTRICAL REQUIREMENTS</b>	
3.1 POWER SUPPLY.....	10
3.2 PROTECTION .....	10
3.3 ELECTROMAGNETIC COMPATIBILITY .....	10
3.4 INDICATOR .....	10
3.5 SWITCHES AND ADJUSTMENT FACILITIES.....	11
3.6 CONNECTION FACILITIES FOR INDEPENDENT SENSOR UNITS.....	11
3.7 CONNECTION FACILITIES FOR RACK-MOUNTED SENSOR UNITS .....	13
3.8 CONNECTION FACILITIES FOR INTEGRATED LOOP DETECTORS .....	15
3.9 RELIABILITY .....	16
<b>SECTION 4 OPERATIONAL PERFORMANCE</b>	
4.1 BASIS FOR SPECIFIED PERFORMANCE .....	17
4.2 INDUCTANCE RANGE.....	17
4.3 MINIMUM ACTUATION .....	17
4.4 MAXIMUM ACTUATION .....	17
4.5 SENSITIVITY SETTINGS .....	17
4.6 RESPONSE TIME.....	17
4.7 TURN-OFF TIME .....	17
4.8 RECOVERY TIME .....	18
4.9 PRESENCE TIME.....	18
4.10 PARALYSIS TIME .....	18
4.11 PASSAGE DETECTOR OUTPUT .....	18
4.12 OUTPUT CHARACTERISTICS .....	18
4.13 AUTOMATIC DRIFT COMPENSATION (TRACKING).....	19
4.14 INITIAL POWER-UP OR INTERRUPTION OF ELECTRICITY SUPPLY.....	19
4.15 RECOVERY FROM POSITIVE INDUCTANCE CHANGE .....	19
4.16 FAILURE MODE.....	19
4.17 SURGE PROTECTION.....	20
4.18 VARIATION IN OPERATING CONDITIONS .....	20
4.19 SUSCEPTIBILITY TO INTERFERENCE .....	20
4.20 INTERACTION (CROSSTALK) .....	21
4.21 LEAKAGE TO EARTH .....	21
4.22 OPERATION WITH TRAMS .....	21