



Precast concrete access and maintenance chambers for sewerage applications



AS 4198:2022

This Australian Standard ® was prepared by WS-006, Concrete Pipes. It was approved on behalf of the Council of Standards Australia on 4 March 2022.

This Standard was published on 18 March 2022.

The following are represented on Committee WS-006:

Australian Chamber of Commerce and Industry
Australian Institute of Building
Austroads
Concrete Institute of Australia
Concrete Pipe Association of Australasia
Engineers Australia
National Precast Concrete Association Australia

University of New South Wales

Water Services Association of Australia

Additional Interests

Auckland Council Business New Zealand Concrete New Zealand Precast

This Standard was issued in draft form for comment as DR AS 4198:2020.

Keeping Standards up-to-date

Ensure you have the latest versions of our publications and keep up-to-date about Amendments, Rulings, Withdrawals, and new projects by visiting: www.standards.org.au

ISBN 978 1 76113 685 6

This is a preview. Click here to purchase the full publication.

Precast concrete access and maintenance chambers for sewerage applications

First published as AS 4198—1994. Second edition 2022.

© Standards Australia Limited 2022

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Cth).

Preface

This Standard was prepared by the Standards Australia Committee WS-006, Concrete Pipes, to supersede AS 4198:1994, *Precast concrete access chambers for sewerage applications*.

The objective of this Standard is to provide a performance-based document for precast concrete access and maintenance chambers.

The major changes in this edition are as follows:

- (a) Durability has been enhanced with additional requirements covering reinforcement and concrete materials, as well as production, placement and curing of concrete. This edition also introduces a new exposure classification for chambers in sewer applications.
- (b) Precast concrete maintenance chambers have been incorporated into this Standard.
- (c) An increase in the maximum depth of chambers and the maximum nominal diameter of chambers and an increase in the maximum diameter of connecting pipes. Additional testing requirements and test methods have been included that accompany these changes in diameter and depth.
- (d) Updates to the load testing requirements to accommodate larger diameter chambers and also changes in road traffic loading from AS 5100.2:2017.
- (e) A new informative appendix has been added to provide guidance on the installation of precast access and maintenance chamber systems.

Statements in alphabetical superscript footnotes in tables expressed in mandatory terms are deemed to be requirements of this document. Other notes are only for information and guidance.

The terms "normative" and "informative" are used in Standards to define the application of the appendices to which they apply. A "normative" appendix is an integral part of a Standard, whereas an "informative" appendix is only for information and guidance.

Contents

Preface		ii
Introducti	on	vi
Section 1	Scope and general	1
1.1	Scope	
1.2	Normative references	
1.3	Terms and definitions	
Section 2	Component structure, manufacture and materials	11
2.1	General	11
2.2	Exposure classification	
	2.2.1 Exposure classification for internal environments	
	2.2.2 Exposure classification of the external environment	
2.3	Concrete materials	
	2.3.1 Cementitious materials	
	2.3.2 Cementitious material for concrete	
	2.3.3 Aggregates	
	2.3.4 Water	
	2.3.5 Admixtures	
	2.3.6 Reinforcement	
	2.3.7 Synthetic fibres 2.3.8 Restrictions on chemical content	
	2.3.9 Minimum cementitious material content, maximum water / cementitious	10
	material ratio, and maximum water absorption value	1Ω
	2.3.10 Alternative concrete mixes	10 18
2.4	Cover to reinforcement	
2.1	2.4.1 General	
	2.4.2 Cover to reinforcement for internal environment	
	2.4.3 Cover to reinforcement to the external environment	
	2.4.4 Cover to reinforcement for mating surfaces of joints between components	
	2.4.5 Additional concrete requirements for internal and external environments	21
2.5	Manufacturing processes, and concrete production, placement and curing	
	2.5.1 Manufacturing processes	
	2.5.2 Concrete batching	
	2.5.3 Concrete placing	
	2.5.4 Curing	
2.6	Concrete quality control testing	
	2.6.1 Machine-made concrete testing	
	2.6.2 Wet cast concrete and automated SCC cast concrete testing	
2.7	Elastomeric seals	
	2.7.1 General	
	2.7.2 Mastic sealants	
	2.7.3 Other materials	∠ /
Section 3	Manufacture, workmanship and finish	
3.1	General	
3.2	Test loads for proof and ultimate load testing	
	3.2.1 General	
	3.2.2 Vertical load testing requirements	
	3.2.3 Horizontal load testing requirements (shaft components only)	
3.3	Dimensions and tolerances	
	3.3.1 Internal diameter of shafts	
	3.3.2 Access cover clear opening sizes.	
3.4	Measurement of the dimensions 3.4.1 Straightness	
	3.4.2 Squareness of ends	
	or in oquar circoo or circo	

	3.4.3 Shaft diameter	
	3.4.4 Wall thickness	
	3.4.5 Effective length	
	3.4.6 Slab thickness	
3.5	Workmanship and finish	
	3.5.1 General	
	3.5.2 Joints	
	3.5.3 Reinforcement	
	3.5.4 Cover	
	3.5.5 Classification of defects	
3.6	Marking	
3.7	Handling and storage	
	3.7.1 General	
	3.7.2 Lifting inserts	
	3.7.3 Unreinforced access and maintenance chamber components	36
Section 4	Step irons and ladders	37
4.1	General	37
4.2	Materials	
4.3	Performance testing of installed step irons	
4.4	Step-up and step-down limitations	
	4.4.1 Step-up	
	4.4.2 Step-down	
Cootion F	•	
Section 5	Access covers and frames	
5.1	General Source of Grainly	
5.2	Surface finish	
5.3	Design of lifting keyholes	40
Section 6	Sampling and testing of access and maintenance chamber components	41
6.1	General	41
	6.1.1 Facilities for sampling and testing	41
	6.1.2 Testing procedures	
	6.1.3 Testing	
6.2	Type testing	
	6.2.1 General	
	6.2.2 Manufacture	
	6.2.3 Test specimens	45
6.3	Routine testing	
	6.3.1 General	
	6.3.2 Sampling	
	6.3.3 Testing	
6.4	Test requirements	
	6.4.1 Ultimate load	
	6.4.2 Proof load	
	6.4.3 Cover to reinforcement	
	6.4.4 Water absorption	
	6.4.5 Hydrostatic testing of shafts and base units	
	6.4.6 Hydrostatic testing of joints	
	6.4.7 Vacuum testing of shafts and base units	
	6.4.8 Vacuum testing of joints	
	6.4.9 Hydrostatic testing of the base to pipe joints	
	6.4.10 Dimensional accuracy	
	6.4.11 Step irons	47
Appendix A	A (normative) Product conformity	48
	3 (informative) Information exchange between manufacturer and purchaser	
Appendix (C (normative) Methods for load testing of access and maintenance chamber	

Appendix D (normative) Method for cover testing of reinforced precast concrete access and maintenance chamber components	72
Appendix E (normative) Method for water absorption testing	74
Appendix F (normative) Method for hydrostatic testing of a shaft section	78
Appendix G (normative) Method for hydrostatic testing of a shaft assembly joint	81
Appendix H (normative) Method for load testing of step irons and ladders	84
Appendix I (informative) Guide to determining exposure classification	86
Appendix J (normative) Method for vacuum testing of a shaft section	88
Appendix K (normative) Method for vacuum testing of a jointed shaft assembly	91
Appendix L (informative) Method for leak testing of a base to pipe joint seal	94
Appendix M (informative) Installation	98
Appendix N (normative) Accelerated curing of wet-cast concrete components	102
Bibliography	105

AS 4198:2022

Introduction

This Standard was prepared by the Standards Australia Committee WS-006, Concrete Pipes, as a performance-based document for precast concrete access and maintenance chambers.

vi

It was prepared to address advances in current practice, the age of the previous publication of AS 4198 and proposals from industry to move towards greater use of product performance testing. This Standard specifies product performance requirements and excludes normative installation procedures. However, this Standard provides an informative procedure for installation. For further guidelines on recommended installation procedures, reference should be made to the relevant published literature of access and maintenance chamber manufacturers, asset owners, asset owner industry associations and, where appropriate, regulatory authorities.

The in-service life of a precast concrete access or maintenance chamber is dependent on the manufacture, application and installation conditions. This Standard intends that for such installations, service life of 100 years could be expected when components are manufactured in accordance with and installed as recommended by this Standard in the environments defined in this Standard. Components subject to other environments should be assessed for suitability using appropriate engineering judgement. The Standard specifies requirements for concrete access cover assemblies and excludes requirements for metal and polymeric access cover assemblies. The use of some blended cement and chemical admixtures in concrete components is addressed by the Standard.

This document specifically addresses sewerage applications but may also be relevant to drainage, stormwater and other conveyance applications.

Australian Standard®

Precast concrete access and maintenance chambers for sewerage applications

Section 1 Scope and general

1.1 Scope

This Standard describes performance requirements for circular precast concrete access and maintenance chambers systems including chamber materials, component manufacture and quality control. It also describes methods of sampling and testing of precast concrete components manufactured in accordance with the Standard.

This Standard applies to precast concrete access and maintenance chamber components manufactured from steel reinforced, synthetic fibre reinforced or unreinforced concrete that are intended for use in buried sewerage systems. Access chambers conforming to the requirements of this Standard are suitable for a maximum depth to invert of 9 m and to a typical connected pipe diameter not larger than DN750. Similarly, maintenance chambers are suitable for a maximum depth of 6 m and a connecting pipe diameter of not more than DN300.

For other circumstances where depths are greater than 9 m, then specific design matters should be addressed between the designer and the manufacturer.

NOTE 1 Information on means for demonstrating conformity to this Standard is given in Appendix A.

NOTE 2 Guidance on the information to be exchanged by purchaser and manufacturer at the time of an access or maintenance chamber product enquiry or order is given in Appendix B.

NOTE 3 Special design considerations, including high water table, buoyancy uplift resistance, chamber depths greater than 9 m and connected pipes that exceed 750 mm in diameter should be addressed by negotiation between the parties.

NOTE 4 Guidance on the installation of precast access and maintenance chamber systems, including excavation, foundation preparation, placing of units, backfilling, compaction and *in situ* testing is provided in an informative Appendix M.

This Standard does not provide for the following:

- (a) Requirements for cast *in situ* concrete components.
- (b) Ladders that are supplied and installed *in situ*.
- (c) Plastics maintenance shafts.

1.2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes the requirements of this document.

NOTE Documents referenced for informative purposes are listed in the Bibliography.

AS 1012.1, Methods of testing concrete, Method 1: Sampling of fresh concrete

AS 1012.3.5, Methods of testing concrete, Method 3.5: Determination of properties related to the consistency of concrete — Slump flow, T500 and J-ring test

AS 1012.8.1, Methods of testing concrete, Method 8.1: Method for making and curing concrete — Compression and indirect tensile test specimens

AS 1012.9, Methods of testing concrete, Method 9: Compressive strength tests — Concrete, mortar and grout specimens

AS 1012.12.1, Methods of testing concrete, Method 12.1: Determination of mass per unit volume of hardened concrete — Rapid measuring method

AS 1012.20.1, Methods of testing concrete, Method 20.1: Determination of chloride and sulfate in hardened concrete and aggregates — Nitric acid extraction method

AS 1141.2, Methods for sampling and testing aggregates, Method 2: Basic testing equipment

AS 1141.5, Methods for sampling and testing aggregates, Method 5: Particle density and water absorption of fine aggregate

AS 1141.6.1, Methods for sampling and testing aggregates, Method 6.1: Particle density and water absorption of coarse aggregate — Weighing-in-water method

AS 1141.6.2, Methods for sampling and testing aggregates, Method 6.2: Particle density and water absorption of coarse aggregate — Pycnometer method

AS 1141.60.1, Methods for sampling and testing aggregates, Method 60.1: Potential alkali-silica reactivity — Accelerated mortar bar method

AS 1141.60.2, Methods for sampling and testing aggregates, Method 60.2: Potential alkali-silica reactivity — Concrete prism method

AS 1379, Specification and supply of concrete

AS 1478.1, Chemical admixtures for concrete, mortar and grout, Part 1: Admixtures for concrete

AS 1646, Elastomeric seals for waterworks purposes

AS 1657, Fixed platforms, walkways, stairways and ladders — Design, construction and installation

AS 2193, Calibration and classification of force-measuring systems

AS 2758.1, Aggregates and rock for engineering purposes, Part 1: Concrete aggregates

AS 3500.0, Plumbing and drainage, Part 0: Glossary of terms

AS 3582.2, Supplementary cementitious materials, Part 2: Slag — Ground granulated blast-furnace

AS 3799, Liquid membrane-forming curing compounds for concrete

AS 3850, Prefabricated concrete elements (series)

AS 3972, General purpose and blended cements

AS 3996, Access covers and grates

AS 4586, Slip resistance classification of new pedestrian surface materials

AS 4663, Slip resistance measurement of existing pedestrian surfaces

AS 5100.2, Bridge design, Part 2: Design loads

AS 5100.5, Bridge design, Part 5: Concrete

AS/NZS 1554.3, Structural steel welding, Part 3: Welding of reinforcing steel

AS/NZS 3582.1, Supplementary cementitious materials, Part 1: Fly ash

AS/NZS 3582.3, Supplementary cementitious materials, Part 3: Amorphous silica