GEOTECHNICAL PRACTICE PUBLICATION NO. 5

GEO-VELOPMENT The Role of Geological and Geotechnical Engineering in New and Redevelopment Projects

Edited by Christoph M. Goss, Ph.D., P.E. Richard L. Wiltshire, P.E. Joels C. Malama, P.E. Minal L. Parekh, P.E.





GEOTECHNICAL PRACTICE PUBLICATION NO. 5

GEO-VELOPMENT

THE ROLE OF GEOLOGICAL AND GEOTECHNICAL ENGINEERING IN NEW AND REDEVELOPMENT PROJECTS

PROCEEDINGS OF THE 2008 BIENNIAL GEOTECHNICAL SEMINAR

November 7, 2008 Denver, Colorado

SPONSORED BY The Geo-Institute of the American Society of Civil Engineers

Geotechnical Group of the Colorado Section of the American Society of Civil Engineers

Rocky Mountain Section of the Association of Environmental and Engineering Geologists

Colorado Association of Geotechnical Engineers

EDITED BY Christoph M. Goss, Ph.D., P.E. Richard L. Wiltshire, P.E. Joels C. Malama, P.E. Minal L. Parekh, P.E.





Published by the American Society of Civil Engineers

Library of Congress Cataloging-in-Publication Data.

Biennial Geotechnical Seminar (2008 : Denver, Colo.)

Geo-velopment the role of geological and geotechnical engineering in new and redevelopment projects : proceedings of the 2008 Biennial Geotechnical Seminar, November 7, 2008, Denver, Colorado / sponsored by The Geo-Institute of the American Society of Civil Engineers ; edited by Christoph M. Goss ... [et al.].

p. cm. -- (Geotechnical practice publication ; no. 5)

Includes bibliographical references and index.

ISBN 978-0-7844-1006-6

1. Engineering geology--Colorado--Congresses. 2. Hydraulic engineering--Colorado--Congresses. I. Goss, Christoph M. II. American Society of Civil Engineers. Geo-Institute. III. Title.

TA705.3.C6B54 2008 624.1'5109788--dc22

2008040615

American Society of Civil Engineers 1801 Alexander Bell Drive Reston, Virginia, 20191-4400

www.pubs.asce.org

Any statements expressed in these materials are those of the individual authors and do not necessarily represent the views of ASCE, which takes no responsibility for any statement made herein. No reference made in this publication to any specific method, product, process, or service constitutes or implies an endorsement, recommendation, or warranty thereof by ASCE. The materials are for general information only and do not represent a standard of ASCE, nor are they intended as a reference in purchase specifications, contracts, regulations, statutes, or any other legal document. ASCE makes no representation or warranty of any kind, whether express or implied, concerning the accuracy, completeness, suitability, or utility of any information, apparatus, product, or process discussed in this publication, and assumes no liability therefore. This information should not be used without first securing competent advice with respect to its suitability arising from such use, including but not limited to infringement of any patent or patents.

ASCE and American Society of Civil Engineers-Registered in U.S. Patent and Trademark Office.

Photocopies and reprints.

You can obtain instant permission to photocopy ASCE publications by using ASCE's online permission service (<u>http://pubs.asce.org/permissions/requests/</u>). Requests for 100 copies or more should be submitted to the Reprints Department, Publications Division, ASCE, (address above); email: permissions@asce.org. A reprint order form can be found at http://pubs.asce.org/support/reprints/.

Copyright © 2009 by the American Society of Civil Engineers. All Rights Reserved. ISBN 978-0-7844-1006-6 Manufactured in the United States of America.

Cover Photo: 1515 Wynkoop, A Hines Project. Courtesy of Jim Niehoff, P. E. of PSI, Inc.

Preface

Across all lands and time, engineers have developed their environment to obtain housing, water, transportation, mineral resources, and protection. As structures wore out or societal needs changed, the environment would be redeveloped. Inevitably, the development would start from the ground up, in the realm of the geotechnical engineer, who would make the foundation of the dam, building, or canal strong and clean. Geotechnical engineering in Colorado began around the 8th Century A.D. at Mesa Verde, when the first reservoir was constructed by the Ancestral Puebloans. In the 19th Century, geotechnical engineering was focused on mining and irrigation. As cities grew in the 20th Century, the development focus shifted to large buildings, roads, airports, bridges, and dams. Today, Colorado's geo-community continues its work to develop new areas and re-develop the old. We hope that this collection of seminar papers, presenting Colorado's geotechnical practice and experience related development and re-development, will be of value to others worldwide.

Since 1984, the ASCE Colorado Section's Geotechnical Group, in collaboration with the Rocky Mountain Section of the Association of Environmental and Engineering Geologists and the Colorado Association of Geotechnical Engineers, has organized a biennial series of geotechnical seminars on a wide variety of themes that have been attended by as many as 270 civil/geotechnical engineers, geologists, and other geoprofessionals. The geotechnical seminars have been held at area universities or hotels and have offered the opportunity for sharing ideas and experiences among Colorado's diverse geo-disciplines. Since 2004, ASCE's Geo-Institute has published the papers of these seminars in Geotechnical Practice Publications, allowing the experiences to be shared with a worldwide audience.

The GEO-velopment Steering Committee convened in August 2007 and held monthly meetings to plan for the 2008 Biennial Geotechnical Seminar. The Steering Committee members included Joels Malama (Conference Chair), Dr. Christoph Goss, Mark Brooks, Dr. Bill McCarron, Minal Parekh, Becky Roland, Mark Vessely, Leslie Jansen, Steve Bryant, Jere Strickland, Keith Seaton, Melanie Longi, Joe Kerrigan, Chris Wienecke, and Richard Wiltshire.

Christoph Goss, Richard Wiltshire, Joels Malama, and Minal Parekh

Acknowledgements

The GEO-velopment Steering Committee wishes to take this opportunity to thank all of the authors and reviewers of our papers, which are herein presented as Geotechnical Practice Publication No. 5. The authors have spent many hours in preparing and finalizing their papers, which will be presented at the 2008 Biennial Geotechnical Seminar on November 7, 2008. These papers have been reviewed by a volunteer group of Denver area geo-professionals who put in their valuable time and helped make these papers even better. The Geo-Institute's Committee on Technical Publications completed its review of our GEO-velopment papers in a very timely manner and their adherence to our aggressive publication schedule is greatly appreciated. We would also like to acknowledge the assistance of Donna Dickert of ASCE's Book Production Department for putting this publication together.

Contents

Solving Complex Geotechnical Problems

Downtown Redevelopment with Complex Site Constraints
Development Constraints in Areas with Sugar Beet Spoils
Ground Modification by Sub-Excavation for Subdivisions on Expansive Soils
Dams and Water Resources
Remedial Measures for Spillway Stability Problem on the Colorado Front Range 38 Gokhan Inci, Dale M. Baures, and Michael J. Miller
Sinkhole Remediation and Geomembrane Lining of RCC Reservoir No. 1
Transient Seepage Analysis of Soil-Cement Uplift Pressures during Reservoir Drawdown
Considerations for Detection of Internal Erosion in Embankment Dams
Reservoir Embankments of Mesa Verde

Remediation and Innovation

Brownfield Development Challenges at a Former Manufacturing Facility,	
Engineering "Opportunities" Make the Difference	
Jon Friedman and Ken Elliott	
Chilled Mirror Measurements of Soil Water Retention Curves Harold W. Olsen, Kerry Repola, and Christopher J. Wienecke	127
Modeling the Effects of Intrinsic Damping in Soil-Structure Interaction Judith Wang	142

Earth Retention

Asset Management Sys	stems for Retainin	ng Walls10	62
Scott A. Anderson	Daniel Alzamora,	, and Matthew J. DeMarco	

Case History—Southlands Orchard Road Retaining Walls	178
Garfield County Regional Airport Runway Upgrade Project	192
Indexes	
Subject Index)5

Downtown Redevelopment with Complex Site Constraints

James W. Niehoff¹, M. ASCE, P.E.

¹Chief Engineer, Professional Service Industries, Inc., 451 East 124th Avenue, Thornton, Colorado 80241; jim.niehoff@psiusa.com

ABSTRACT: When a developer selected a site in Denver for a new office building, there were numerous challenges to be faced. Due to zoning and height restrictions, the 8 story building required 4 levels of below grade parking, extending over 6 meters (20 feet) below the water table in coarse sand. On the northwest and southwest sides of the site, an existing basement wall was present at the property line, supporting critical utilities in the backfill zone. On the northeast side of the site, a portion of a newly completed building was supported on shallow footing foundations located about 6 meters (20 feet) above final proposed grade at the property line. As the new building was to extend to the property line, there was no room for a temporary excavation bracing system. All of these factors dictated a creative approach to site preparation and building construction. The ultimate approach to construction involved the installation of a secant wall around the entire periphery of the site, extending into bedrock to cut off the majority of the groundwater, provide lateral and vertical support for the adjoining building.

INTRODUCTION

During the past few years, the Lower Downtown section of Denver, Colorado has experienced a period of significant development and redevelopment. Once a predominantly commercial/warehouse district, the area now includes Coors Field (a major league baseball park), as well as numerous shops, restaurants, condominiums, and offices.

While older buildings dating to the 1800's largely have been refurbished and converted to new use, a few more recently constructed buildings with less historical significance have been razed to make way for new development. One such building was the former United States Post Office Processing Center located within the city block bordered by 15th, Wynkoop, 16th and Wewatta Streets at the western extreme of the Lower Downtown District. This large, utilitarian structure was constructed in the middle part of the 20th Century and included one to two basement levels and 4 levels above grade (Figure 1). Following acquisition of the property by a national developer,

the building was demolished to street level and the basements were filled with the resulting demolition debris.



Figure 1: Post Office Processing Center

Due to the large size of the site, it was subdivided into two parcels. The northeastern half was developed first, with an 8 story office building, currently housing the Denver Office of the Environmental Protection Agency (EPA). This entire parcel incorporated 2 levels of below-grade parking. The overlying 8-story office has a slightly smaller footprint, leaving an at grade access drive along the southwestern property line. This office building is primarily supported by drilled pier foundations extending into the Denver Formation bedrock. However, the exterior wall of the parking deck running along the shared southwestern property line was supported by a strip footing foundation bearing at a depth of about 7 meters (22 feet) below adjacent street grades.

Following substantial completion of the EPA building, plans were developed for construction of a second office building on the remaining parcel of land. This was also to be an 8-story office building to house a prominent local insurance company. Due to local building height restrictions and tenant requirements, plans called for the building to incorporate 4 levels of below-grade parking. This requirement would ultimately create significant complications for the project and necessitate innovative approaches to both design and construction.

PROJECT CHALLENGES

The 1515 Wynkoop Project, as it was ultimately designated, faced a number of significant challenges including high groundwater, the presence of existing structural elements, and the need to protect adjacent sensitive utilities and structures during and after construction.

The subsurface profile in the project site area consists of Quaternary-aged alluvial sands and gravels extending to depths of about 13 to 14 meters (40 to 45 feet) below

GEO-velopment

grade atop the Denver Formation (Niehoff, 2006). The bedrock consists of weakly to moderately cemented sandstone/claystone which extends to a depth of over 100 meters (300 feet). The Denver Formation materials are relatively impervious, and as a result, support aerially extensive perched groundwater. The system is recharged locally by the infiltration of surface water through the pervious surficial sands and by Cherry Creek, which is located two blocks to the south of the site. While fluctuations in the water table occur seasonally, groundwater is typically found about 8 to 9 meters (24 to 27 feet) below the level of the surrounding streets. Given that the parking levels would need to extend to a depth of 13 to 15 meters (40 to 45 feet) below street level, groundwater would need to be considered both during and after building construction.

The post office building that had previously occupied the site had been supported by a system of footing foundations bearing in dense sand strata at the approximate level of the groundwater system. The foundations around the periphery of the building extended to the property line and supported a thick reinforced concrete basement wall. The foundations and basement walls had been left in-place during building demolition and the open basement areas had been filled with construction debris. New construction would require excavations to depths of over 6 meters (20 feet) below the bearing elevations of the existing foundations and the base of this wall. Due to the presence of critical utilities, including fiber optic cables, water and gas lines within 1 to 2 meters (3 to 5 feet) of the existing basement walls, it would not be possible to install a new excavation bracing system at the property line to allow for the removal of these basement walls.

The new structure was also designed to extend to the site's northeastern property line. This would require a cut extending to a depth of over 6 meters (20 feet) below the footing foundations supporting the exterior wall of the EPA building parking structure. A section through the site presenting this geometry is presented on Figure 2, below.



Figure 2: Section though the site presenting project geometry

This is a preview. Click here to purchase the full publication.
