

Flood Resistant Design and Construction

This document uses both the
International System of Units (SI)
and customary units

American Society of Civil Engineers

Flood Resistant Design and Construction

This document uses both the International System of Units (SI) and customary units.



Published by the American Society of Civil Engineers

This is a preview. [Click here to purchase the full publication.](#)

Library of Congress Cataloging-in-Publication Data

Flood resistant design and construction.

pages cm

“ASCE/SEI 24-14.”

ISBN 978-0-7844-1379-1 (print : alk. paper)—ISBN 978-0-7844-7872-1 (ebook)

1. Structural design—Standards. 2. Flood damage prevention—United States.
 3. Building, Stormproof—United States. I. American Society of Civil Engineers.
- TA658.2.F56 2015
624.1'76—dc23

2014035187

Published by American Society of Civil Engineers

1801 Alexander Bell Drive

Reston, Virginia, 20191-4382

www.asce.org/bookstore | ascelibrary.org

This standard was developed by a consensus standards development process that has been accredited by the American National Standards Institute (ANSI). Accreditation by ANSI, a voluntary accreditation body representing public and private sector standards development organizations in the United States and abroad, signifies that the standards development process used by ASCE has met the ANSI requirements for openness, balance, consensus, and due process.

While ASCE's process is designed to promote standards that reflect a fair and reasoned consensus among all interested participants, while preserving the public health, safety, and welfare that is paramount to its mission, it has not made an independent assessment of and does not warrant the accuracy, completeness, suitability, or utility of any information, apparatus, product, or process discussed herein. ASCE does not intend, nor should anyone interpret, ASCE's standards to replace the sound judgment of a competent professional, having knowledge and experience in the appropriate field(s) of practice, nor to substitute for the standard of care required of such professionals in interpreting and applying the contents of this standard.

ASCE has no authority to enforce compliance with its standards and does not undertake to certify products for compliance or to render any professional services to any person or entity.

ASCE disclaims any and all liability for any personal injury, property damage, financial loss, or other damages of any nature whatsoever, including without limitation any direct, indirect, special, exemplary, or consequential damages, resulting from any person's use of, or reliance on, this standard. Any individual who relies on this standard assumes full responsibility for such use.

ASCE and American Society of Civil Engineers—Registered in U.S. Patent and Trademark Office.

Photocopies and permissions. Permission to photocopy or reproduce material from ASCE publications can be requested by sending an e-mail to permissions@asce.org or by locating a title in ASCE's Civil Engineering Database (<http://cedb.asce.org>) or ASCE Library (<http://ascelibrary.org>) and using the “Permissions” link.

Errata: Errata, if any, can be found at <http://dx.doi.org/10.1061/9780784413791>.

Copyright © 2015 by the American Society of Civil Engineers.

All Rights Reserved.

ISBN 978-0-7844-1379-1 (print)

ISBN 978-0-7844-7872-1 (PDF)

Manufactured in the United States of America.

22 21 20 19 18 17 16 15

1 2 3 4 5

ASCE STANDARDS

In 2006, the Board of Direction approved the revision to the ASCE Rules for Standards Committees to govern the writing and maintenance of standards developed by the Society. All such standards are developed by a consensus standards process managed by the Society's Codes and Standards Committee (CSC). The consensus process includes balloting by a balanced standards committee made up of Society members and nonmembers, balloting by the membership of the Society as a whole, and balloting by the public. All standards are updated or reaffirmed by the same process at intervals not exceeding five years.

The material presented in this Standard has been prepared in accordance with recognized engineering principles. This

Standard should not be used without first securing competent advice with respect to its suitability for any given application. The publication of the material contained herein is not intended as a representation or warranty on the part of the American Society of Civil Engineers, or of any other person named herein, that this information is suitable for any general or particular use or promises freedom from infringement of any patent or patents. Anyone making use of this information assumes all liability from such use.

A complete list of currently available standards is available in the ASCE Library (<http://ascelibrary.org/page/books/s-standards>).

This page intentionally left blank

PREFACE

The material presented in this standard has been prepared in accordance with recognized engineering principles. This standard should not be used without first securing competent advice with respect to its suitability for any given application. The publication of the material contained herein is not intended as a representation or warranty on the part of the American Society of Civil Engineers, or of any other person named herein, that this information is suitable for any general or particular use or promises freedom from infringement of any patent or patents. Anyone making use of this information assumes all liability from such use.

The 2014 edition has a number of significant technical revisions from the 2005 edition, including

1. Defines Flood Design Class rather than using Risk/Occupancy Classification assigned under ASCE 7 and requires each building or structure governed by the standard to be assigned to Flood Design Class 1, 2, 3, or 4. Uses the assigned Flood Design Class to apply elevation requirements specified in Chapters 2, 4, 5, 6, and 7. Flood Design Class 4 buildings and facilities are equivalent to Occupancy Category/Risk Category IV buildings, which ASCE 7 identifies as essential facilities.
2. Adds definitions for Mixed Use and Residential Portions of Mixed Use in commentary to clarify limitations on use of dry floodproofing measures.
3. Changes the Coastal A Zone determination requirement from the designer's responsibility to one depending on either: (1) delineation of a Limit of Moderate Wave Action (LiMWA) on a Flood Insurance Rate Map, or (2) designation by the Authority Having Jurisdiction.
4. Separates specifications for flood openings from the installation requirements. Requires the presence of louvers, blades, screens, faceplates, or other covers and devices to be accounted for in determining net open area for non-engineered openings and in determining the performance of engineered openings. Revises coefficient of discharge table for engineered flood openings. Adds commentary regarding selection of coefficient of discharge and for grouping or stacking of flood openings.
5. For Flood Design Class 4 buildings, requires the minimum lowest floor elevation (or floodproofing level of protection) to be the higher of the Base Flood Elevation plus freeboard specified in Chapters 2, 4, and 6, the Design Flood Elevation, or the 500-year flood elevation. The 500-year flood elevation requirement is new.
6. Clarifies text pertaining to alluvial fan high risk flood hazard areas.
7. In Coastal High Hazard Areas (V Zone) and Coastal A Zones (if delineated),
 - a. Makes explicit that designs must account for local scour and erosion
 - b. Provides for shallow foundations in Coastal A Zones under certain circumstances
 - c. Requires flood openings in breakaway walls
 - d. Eliminates orientation of the lowest horizontal structural member as a factor to determine elevation for lowest floors, equipment, and flood damage-resistant materials
 - e. Requires exterior doors at the top of stairways that are located inside enclosed areas with breakaway walls
 - f. Consolidates requirements for all nonstructural concrete slabs
 - g. Allows substantial improvement of existing buildings seaward of the reach of mean high tide in V zones (makes ASCE 24 consistent with National Flood Insurance Program and Coastal A Zones).
8. Updates flood damage-resistant material requirements.
9. Clarifies emergency escape and rescue opening requirements for dry floodproofed buildings.
10. Clarifies requirements for garages, carports, and accessory storage structures. Adds new section for multistory parking structures.
11. Consolidates requirements for tanks and more clearly distinguishes between requirements based on flood hazard area.

This page intentionally left blank

ACKNOWLEDGMENTS

The American Society of Civil Engineers (ASCE) acknowledges the work of the Flood Resistant Design and Construction Standard Committee of the Codes and Standards Activities Division of the Structural Engineering Institute. This group comprises individuals from many backgrounds including consulting engineering, research, construction, education, government, design, and private practice.

This standard was prepared through the consensus standards process by balloting in compliance with procedures of ASCE's Codes and Standards Activities Committee. Those individuals who served on the ASCE 24-14 Standard Committee include

Christopher P. Jones, P.E., M.ASCE, Chair
Larry Buss, P.E., D.WRE, M.ASCE, CFM
Russell J. Coco, P.E., M.ASCE
James P. Colgate, RA, Esq., CFM
William L. Coulbourne, P.E., M.ASCE, F.SEI
James B. Destefano, P.E., AIA, F.SEI
Gary J. Ehrlich, P.E., M.ASCE
Shou-Shan Fan, Ph.D.
Kenneth J. Filarski, FAIA, AICP, LEED-AP BD+C, CFM, SAP+AEER, NCARB
Daryle L. Fontenot, P.E., CFM

Carol Friedland, Ph.D., P.E., CFM
Michael J. Graham, CFM
John L. Ingargiola, EI, CBO, CFM
Catherine M. Kaake, P.E., M.ASCE
Philip Line, P.E., M.ASCE
E. Michael McCarthy, P.E., M.ASCE
Joseph J. Messersmith, Jr., P.E., M.ASCE
Kimberly Paarlberg, P.A.
John Squerciati, P.E., CFM, M.ASCE
Terri L. Turner, AICP, CFM
Robert A. Wessel, Ph.D., F.ASTM
Thomas G. Williamson, P.E., F.ASCE, F.SEI
Garland Wilson, P.E., M.ASCE

ASCE would like to thank each member of the committee for his or her dedication and hard work during completion of ASCE 24-14.

ASCE would like to acknowledge the long-standing contributions of previous Committee Chair, Harry B. Thomas, and of those current members who have served the committee since the development of the 1998 edition: William L. Coulbourne, Shou-Shan Fan, Christopher P. Jones, Joseph J. Messersmith, Jr., and Kimberly Paarlberg.

This page intentionally left blank

UNIT CONVERSIONS

Measurement	S.I. Units	Customary Units
Abbreviations	m = meter (S.I. base unit of length) cm = centimeter km = kilometer ha = hectare L = liter (S.I. base unit of volume) mL = milliliter kg = kilogram (S.I. base unit of mass) g = gram N = Newton (m·kg·s ⁻²) Pa = Pascal (N/m ²) kPa = kilopascal J = Joule W = watt kW = kilowatt s = second (S.I. base unit of time) min = minute h = hour day °C = degrees Celsius ppm = parts per million	yd = yard in. = inch mi = mile acre gal = gallon qt = quart lb = pound oz = ounce lbf = pound-force (lb/ft) psi = pounds per square inch atm = atmosphere ft·lbf = feet per pound-force Btu = British thermal unit hp = horsepower s = second min = minute h = hour day °F = degrees Fahrenheit ppm = parts per million
Length	1 m = 3.2808 ft = 1.0936 yd 1 cm = 0.3937 in. 1 km = 0.6214 mile	1 ft = 0.333 yd = 0.3048 m 1 in. = 2.54 cm 1 mile = 0.869 nautical mile = 1.6093 km
Area	1 m ² = 10.7643 ft ² 1 km ² = 0.3861 mi ² 1 ha = 2.4710 acre	1 ft ² = 0.0929 m ² 1 mi ² = 2.59 km ² 1 acre = 43,560 ft ² = 0.4047 ha
Volume	1 L = 0.2642 gal 1 ml = 1 cm ³	1 gal = 4 qt = 3.7854 L 1 ft ³ = 7.481 gal = 28.32 L
Mass	1 g = 0.0353 oz 1 kg = 2.2046 lb	1 oz = 28.3495 g 1 lb = 0.4536 kg
Force	1 N = 0.2248 lb/ft	1 lbf = 4.4482 N
Density	1 kg/m ³ = 0.2048 lb/ft ³ 1 kg/m ³ = 6.2427 lb/ft ³	1 lb/ft ³ = 4.882 kg/m ³ 1 lb/ft ³ = 16.018 kg/m ³
Pressure	1 kPa = 0.145 psi	1 psi = 6.8948 kPa 1 atm = 14.7 psi = 101.35 kPa
Energy and Power	1 J = 1.00 W·s = 0.7376 ft·lbf 1 kJ = 0.2778 W·h = 0.948 Btu 1 W = 0.7376 ft·lbf/s = 3.4122 Btu/h 1 kW = 1,3410 hp	1 ft·lbf = 1.3558 J 1 Btu = 1.0551 kJ 1 ft·lbf/s = 1.3558 W 1 hp = 550 ft·lbf/s = 0.7457 kW
Flow	1 L/s = 15.85 gal/min = 2.119 ft ³ /min	1 gal/min = 0.1337 ft ³ /min = 0.0631 L/s
Concentration	mg/L = ppm _m (in dilute solutions)	
Temperature	°C = (°F - 32) × 5/9	°F = (°C × 9/5) + 32
Fundamental Constants and Relationships	Acceleration of gravity Density of freshwater (at 4 °C) = Density of saltwater (at 15 °C, 35 ppt) = Specific weight of freshwater (15 °C) = Specific weight of saltwater Weight of freshwater Weight of saltwater	32.2 ft/s ² = 9.81 m/s ² 1,000 kg/m ³ = 1 g/cm ³ 1,025 kg/m ³ = 1.025 g/cm ³ 62.4 lb/ft ³ = 9.810 N/m ³ 64.0 lb/ft ³ = 10.062 N/m ³ 1 gal = 8.345 lb = 3.7854 kg 1 gal = 8.559 lb = 3.8825 kg