

# Pavements constructed with clay, natural stone, or concrete pavers —

**Part 8: Guide for the structural design of lightly trafficked pavements of precast concrete flags and natural stone flags**

ICS 93.080.20

Confirmed November 2008
----------------------------

# Committees responsible for this British Standard

The preparation of this British Standard was entrusted to Technical Committee B/507, Paving units and kerbs, upon which the following bodies were represented:

- Brick Development Association
- British Cement Association
- British Ceramic Research Ltd.
- British Precast Concrete Federation Ltd.
- Concrete Society
- County Surveyors' Society
- Department of the Environment, Transport and the Regions (Highways Agency)
- Institution of Civil Engineers
- Interlay (Association of Block Paving)
- Interpave (Concrete Block Paving Association)
- Landscape Institute
- Society of Chemical Industry
- Stone Federation
- Transport Research Laboratory

The following organizations were also represented in the drafting of the standard, through subcommittees B/507/1 and B/507/2:

- British Slate Association
- British Civil Engineering Manufacturers' Association
- Department of the Environment, Transport and the Regions (Building Research Establishment)
- Ministry of Defence

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 19 March 2003

© BSI 19 March 2003

## Amendments issued since publication

Amd. No.	Date	Comments

The following BSI references relate to the work on this British Standard:  
Committee reference B/507  
Draft for comment 01/102974 DC

ISBN 0 580 41295 4

# Contents

	Page
Committees responsible	Inside front cover
Foreword	ii
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Materials	2
5 General design	2
6 Design	2
Annex A (informative) Design example	7
Annex B (normative) Overlay pavements	10
Figure 1 — Graph: base design for paving flag overstressing	4
Figure 2 — Graph: base design for subgrade overstressing (400 mm × 400 mm and 450 mm × 450 mm paving units)	5
Figure 3 — Graph: base design for subgrade overstressing (300 mm × 300 mm paving units)	6
Figure A.1 — Graph: base design for paving flag overstressing — Design example	8
Figure A.2 — Graph: base design for subgrade overstressing (400 mm × 400 mm and 450 mm × 450 mm paving units) — Design example	9
Table 1 — Estimated equilibrium CBR values for design	2
Table 2 — Number of commercial vehicles	3
Table 3 — Standard axle conversion	3
Table B.1 — Condition Factor CF1	10
Table B.2 — Condition Factor CF2	10