



BSI Standards Publication

Pavements constructed with clay, natural stone or concrete pavers

Part 13: Guide for the design of permeable pavements constructed with concrete paving blocks and flags, natural stone slabs and setts and clay pavers

Publishing and copyright information

The BSI copyright notice displayed in this document indicates when the document was last issued.

© BSI 2009

ISBN 978 0 580 58077 2

ICS 93.080.20

The following BSI references relate to the work on this standard:

Committee reference B/507

Draft for comment 07/30159351 DC

Publication history

First published March 2009

Amendments issued since publication

Date	Text affected
------	---------------

Contents

Foreword *iii*

1	Scope	1
2	Normative references	1
3	Terms and definitions	2
4	General design criteria	3
5	Design	9
6	Selection of pavement components	16

Annexes

Annex A (normative) Grading recommendations for base, laying course and joint filling material 20

Annex B (informative) Typical physical properties of replacement systems (geo-cellular) units 22

Annex C (informative) Typical filter fabric specification used in the upper layer 23

Annex D (informative) A structural design example 24

Bibliography 26

List of figures

Figure 1 – Typical location of geotextile 3

Figure 2 – Typical section of total infiltration construction (System A) 4

Figure 3 – Typical section of partial infiltration (System B) 5

Figure 4 – Typical section of no infiltration construction (System C) 6

Figure A.1 – Grading curve example 21

List of tables

Table 1 – Guidance on selection of a pavement system 8

Table 2 – Soil classification guide 8

Table 3 – Sub-base thickness for System A 11

Table 4 – Sub-base thickness for System C 11

Table 5 – Sub-base thickness for System C collecting impermeable area 12

Table 6 – Loading categories 13

Table 7 – System A and B – selection of pavement course material and thickness 14

Table 8 – System C – selection of pavement course material and thickness 14

Table 9 – Additional thickness of coarse graded material for System A and System B 15

Table 10 – Total thickness of capping material for System C 15

Table 11 – Determination of standard axles using the base as a service road 16

Table 12 – Determination of DBM thickness for total number of standard axles 16

Table A.1 – Sub-base grading 20

Table A.2 – Laying course and jointing material grading 20

Table A.3 – Physical property recommendation for CGA 21

Table B.1 – Typical physical properties 22

Table C.1 – Filter fabric specification 23

Summary of pages

This document comprises a front cover, an inside front cover, pages i to iv, pages 1 to 26, an inside back cover and a back cover.

