

Steel wire for the reinforcement of concrete products — Specification

ICS 77.140.15; 91.080.40

Committees responsible for this British Standard

The preparation of this British Standard was entrusted by Technical Committee ISE/9, Steel for concrete reinforcement, to Subcommittee ISE/9/1, Bars, wire and fabric for concrete reinforcement, upon which the following bodies were represented:

British Coatings Federation
British Precast Concrete Federation
Concrete Society
Department of Transport — Highways Agency
Galvanizers Association
Institution of Structural Engineers
UK Certification Authority for Reinforcing Steels
UK Steel Association

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 September 2005

© BSI 2007

First published August 1969
First revision November 1985
Second revision September 2005

Amendments issued since publication

Amd. No.	Date	Comments
17104	30 April 2007	See foreword

The following BSI references relate to the work on this British Standard:
Committee reference ISE/9/1
Draft for comment
04/30109893 DC

ISBN 0 580 46588 8

Contents

	Page
Committees responsible	Inside front cover
Foreword	ii
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols	4
5 Designations	5
6 Steelmaking and manufacturing processes	5
7 Product characteristics	5
8 Evaluation of conformity	10
9 Test methods	12
10 Identification	13
11 Verification of properties in the case of dispute	13
Annex A (normative) Bond test for ribbed and indented steel wire — Beam test	14
Annex B (normative) Identification requirements	22
Bibliography	24
Figure 1 — Rib geometry example with two rows of transverse ribs	8
Figure 2 — Indentation geometry (example with three rows of indentations)	9
Figure A.1 — Dimensions of the hinge for beam type A ($d < 16$ mm)	14
Figure A.2 — Dimensions of the hinge for beam type B ($d \geq 16$ mm)	15
Figure A.3 — Beam test type A ($d < 16$ mm)	15
Figure A.4 — Beam test type B ($d \geq 16$ mm)	16
Figure A.5 — Bond test type A ($d < 16$ mm) — Reinforcement of beam specimens	18
Figure A.6 — Bond test type B ($d \geq 16$ mm) — Reinforcement of beam specimens	19
Figure B.1 — Example of manufacturer's identification mark (using widened ribs)	22
Table 1 — List of symbols	4
Table 2 — Chemical composition (maximum % by mass)	5
Table 3 — Characteristic tensile properties	6
Table 4 — Nominal cross-sectional area and mass per metre of preferred diameters	7
Table 5 — Ranges for rib parameters	8
Table 6 — Characteristic relative rib area	8
Table 7 — Ranges for the indentation parameters	9
Table 8 — Depth of indentations	9
Table 9 — Absolute minimum values of tensile properties	10
Table 10 — Coefficient k as a function of the number n of test results (for a reliable failure rate of 5 % [$p = 0.95$] at a probability of 90 %)	12
Table 11 — Coefficient k as a function of the number (n) of test results (for a reliable failure rate of 10 % [$p = 0.90$] at a probability of 90 %)	12
Table A.1 — Series of reinforcing wire diameters for testing of bond	16
Table B.1 — Identification of the country of origin	23