BS 6349-1-4:2021



BSI Standards Publication

Maritime works

Part 1-4: General — Code of practice for materials



Publishing and copyright information

The BSI copyright notice displayed in this document indicates when the document was last issued.

© The British Standards Institution 2021

Published by BSI Standards Limited 2021

ISBN 978 0 539 12225 1

ICS 93.140; 47.020.01

The following BSI references relate to the work on this document: Committee reference CB/502 Draft for comment 21/30406692 DC

Amendments/corrigenda issued since publication

Date

Text affected

© THE BRITISH STANDARDS INSTITUTION 2021 - ALL RIGHTS RESERVED

Contents		Page
	Foreword	iv
	Section 1: General	1
	Introduction	1
1	Scope	1
2	Normative references	1
3	Terms, definitions and abbreviated terms	5
	Section 2: Concrete	7
4	General recommendations for concrete	7
5	Design and construction of concrete structures	7
6	Durability of concrete structures	8
7	Deterioration processes in concrete structures	9
7.1	General	9
	Table 1 — Limiting values for composition and properties for both reinforced and unreinforced	
	concrete with normal-weight aggregates exposed to both UK seawater conditions and abrasion	
	for a required design working life up to 100 years ^{A) B)}	10
7.2	Chloride-induced corrosion	10
	Table 2 — Maritime exposure classes for chloride induced corrosion of steel in concrete	
	by seawater	11
	Table 3 — Maximum water/cement ratio ⁴³ , minimum cement/combination content ⁵³ and	
	indicative compressive strength class ^{6,1} for normal-weight concrete ^{6,1} of 20 mm maximum	
	aggregate size for reinforced and prestressed ²⁵ concrete exposed to XSM exposure conditions in a	14
	Table 2 Maximum water (compart ratio ^A), minimum compart (combination content ^B) and	14
	Table S = Maximum water/cement ratio5, minimum cement/combination content5, una indicative compressive strength class(1) for normal weight concreteD of 20 mm maximum	
	indicative compressive strength class ⁵ for normal-weight concrete ⁻⁵ of 20 mm maximum	
	temperate climate for an intended working life of up to 30 years (2 of 2)	15
	Table 4 — Maximum water (cement ratio ^{A)} minimum cement (combination content ^{B)} and	15
	indicative compressive strength class ^{C)} for normal-weight concrete ^{D)} of 20 mm maximum	
	agareagte size for reinforced and prestressed ^{E)} concrete exposed to XSM exposure conditions in a	
	temperate climate for an intended working life of up to 50 years (1 of 2)	16
	Table 4 — Maximum water/cement ratio ^{A)} , minimum cement/combination content ^{B)} and	
	indicative compressive strength class ^{C)} for normal-weight concrete ^{D)} of 20 mm maximum	
	aggregate size for reinforced and prestressed ^{E)} concrete exposed to XSM exposure conditions in a	
	temperate climate for an intended working life of up to 50 years (2 of 2)	17
	Table 5 — Maximum water/cement ratio ^{A)} , minimum cement/combination content ^{B)} and	
	indicative compressive strength class ^{C)} for normal-weight concrete ^{D)} of 20 mm maximum	
	aggregate size for reinforced and prestressed ^{E)} concrete exposed to XSM exposure conditions in a	
	temperate climate for an intended working life of up to 100 years (1 of 2)	18
	Table 5 — Maximum water/cement ratio ^{A)} , minimum cement/combination content ^{B)} and	
	indicative compressive strength class ^{C} for normal-weight concrete ^{D} of 20 mm maximum	
	aggregate size for reinforced and prestressed ^{E} concrete exposed to XSM exposure conditions in a	
	temperate climate for an intended working life of up to 100 years (2 of 2)	19
7.3	Carbonation-induced corrosion	13
7.4	Sulfate attack	20
7.5	Delayed ettringite formation (DEF)	20
7.6	Freeze-thaw	20
7.7	Alkali-silica reaction	20
8	Materials and workmanship in concrete structures	21

© THE BRITISH STANDARDS INSTITUTION 2021 - ALL RIGHTS RESERVED I

8.1	General	21
8.2	Chloride content of concrete	21
	Table 6 — Chloride content class of concrete for maritime structures	21
8.3	Reinforcement	21
8.4	Pre-tensioning and post-tensioning systems	22
8.5	Cover	22
8.6	Curing	22
	Table 7 — Minimum curing periods for different cement types	23
8.7	Underwater concreting	23
	Section 3: Metals	25
9	Structural steels and castings	25
9.1	Steel plates and sections	25
9.2	Steel castings	26
9.3	Chains	26
9.4	Cast irons	27
9.5	Corrosion and corrosion mitigation	27
9.6	Protective paints, coatings and wraps	32
9.7	Cathodic protection	35
10	Aluminium and its alloys	36
10.1	General	36
10.2	Structural properties	36
10.3	Corrosion and corrosion protection	37
11	Other metals	37
	Section 4: Timber	38
12	General recommendations for timber	38
13	Resistance to environmental hazards	38
13.1	Mechanical damage	38
13.2	Biological attack	38
13.3	Fungal decay	39
13.4	Marine borers	39
14	Functional suitability	39
14.1	Piling	39
14.2	Superstructures	39
14.3	Kerbs and capping pieces	40
14.4	Fendering and rubbing strips	40
14.5	Sea defences	40
14.6	Dock blocks	40
14.7	Other applications	40
15	Fastenings	40
	Section 5: Polymers	42
16	Elastomers	42
16.1	Rubber	42
	Table 8 — Vulcanized rubber compound physical and mechanical properties	44
16.2	Polyurethane	45
	Table 9 — PTMEG polyurethane elastomer compound physical and mechanical properties	46
16.3	Elastomers for fenders	47
16.4	Elastomers for structural bearings	48
16.5	Embedded/integral steel reinforcing plates	48
17	Plastics	49
17.1	General recommendations for plastics	49

II © THE BRITISH STANDARDS INSTITUTION 2021 - ALL RIGHTS RESERVED

17.2	UHMW-PE	49
	Table 10 — Material properties for UHMW-PE	50
	Section 6: Stone for armouring or protection works	51
18	General recommendations for stone	51
19	Grading	51
19.1	General	51
19.2	Cover layer underlayer and filter applications	51
19.3	Volume filling materials	52
20	Geometrical parameters	52
21	Physical and chemical parameters	53
22	Particular armourstone sources	54
23	Use of stone with concrete armour units	54
	Section 7: Bituminous materials	55
24	Asphaltic concrete	55
25	Sand mastic	57
26	Open stone asphalt	57
27	Lean sand asphalt	59
Annex A	(informative) Factors affecting the design of maritime concrete	60
	Figure A.1 — Schematic diagram of the chloride transport processes in a maritime structure	62
	<i>Figure A.2 — Effect of macroclimate on chloride ingress/induced corrosion</i>	63
Annex B	(informative) Enhanced protection of reinforcement	64
Annex C	(informative) Historically measured corrosion rates	66
	Table C.1 — Measured corrosion rates for non-alloy structural steels in temperate climates	66
Annex D	(informative) Guidance on the specification of materials for elastomeric fenders	67
Annex E	(informative) Typical production control system for elastomeric fenders	69
Annex F	(informative) Uses of bituminous materials	74
	Table F.1 — Possible uses of bituminous materials in maritime protection works	75
	Bibliography	76

Summary of pages

This document comprises a front cover, an inside front cover, pages I to VI, pages 1 to 78, an inside back cover and a back cover.

© THE BRITISH STANDARDS INSTITUTION 2021 - ALL RIGHTS RESERVED III

Foreword

Publishing information

This part of <u>BS 6349</u> is published by BSI Standards Limited, under licence from The British Standards Institution, and came into effect on 31 July 2021. It was prepared by Technical Committee CB/502, *Maritime works*. A list of organizations represented on this committee can be obtained on request to the committee manager.

Supersession

This part of <u>BS 6349</u> supersedes <u>BS 6349-1-4:2013</u>, which is withdrawn.

Relationship with other publications

BS 6349 is published in the following parts:

- Part 1-1: General Code of practice for planning and design for operations;
- Part 1-2: General Code of practice for assessment of actions;
- Part 1-3: General Code of practice for geotechnical design;
- Part 1-4: General Code of practice for materials;
- Part 2: Code of practice for the design of quay walls, jetties and dolphins;
- Part 3: Code of practice for the design of shipyards and sea locks;
- Part 4: Code of practice for design of fendering and mooring systems;
- Part 5: Code of practice for dredging and land reclamation;
- Part 6: Design of inshore moorings and floating structures;
- Part 7: Guide to the design and construction of breakwaters;
- Part 8: Code of practice for the design of Ro-Ro ramps, linkspans and walkways.

Information about this document

This is a full revision of the standard, and introduces the following principal changes.

- a) The standard has been updated to reflect current industry practice. In particular, the concrete section has been updated to be generally in line with the recommendations of <u>BS 8500</u>.
- b) The metals section has been reorganized and updated. In particular, the clauses on corrosion, protective coatings, wraps and cathodic protection have been updated and incorporated into the appropriate section.
- c) A new section on polymers has been added.
- d) The sections on stone for armouring and protective works and bituminous materials have been updated.
- e) The previous clauses on piles, rails, pipes and pavements have been removed from this standard as they are structural elements rather than materials.

Figure A.2 is a reproduction of Figure 6.2 in *Concrete in coastal structures* [1]. It is reproduced with the kind permission of ICE Publishing, 8 Storey's Gate, London SW1P 3AT.

This publication can be withdrawn, revised, partially superseded or superseded. Information regarding the status of this publication can be found in the Standards Catalogue on the BSI website at bsigroup.com/standards, or by contacting the Customer Services team.

IV © THE BRITISH STANDARDS INSTITUTION 2021 - ALL RIGHTS RESERVED

Where websites and webpages have been cited, they are provided for ease of reference and are correct at the time of publication. The location of a webpage or website, or its contents, cannot be guaranteed.

Use of this document

As a code of practice, this part of <u>BS 6349</u> takes the form of recommendations and guidance. It is not to be quoted as if it were a specification. Users are expected to ensure that claims of compliance are not misleading.

Users may substitute any of the recommendations in this part of <u>BS 6349</u> with practices of equivalent or better outcome. Any user claiming compliance with this British Standard is expected to be able to justify any course of action that deviates from its recommendations.

Presentational conventions

The provisions in this standard are presented in roman (i.e. upright) type. Its recommendations are expressed in sentences in which the principal auxiliary verb is "should".

Commentary, explanation and general informative material is presented in smaller italic type, and does not constitute a normative element.

Where words have alternative spellings, the preferred spelling of the Shorter Oxford English Dictionary is used (e.g. "organization" rather than "organisation").

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

Compliance with a British Standard cannot confer immunity from legal obligations.

© THE BRITISH STANDARDS INSTITUTION 2021 - ALL RIGHTS RESERVED V

THIS PAGE DELIBERATELY LEFT BLANK

Section 1: General

Introduction

The materials covered by this part of $\underline{BS\,6349}$ include the basic materials used in civil engineering construction, and composite or manufactured materials where these are normally considered to be materials in their own right.

The materials covered in this part of <u>BS 6349</u> are as follows:

- a) concrete: complementary guidance to BS EN 206, BS 8500-1:2015+A2 and BS 8500-2;
- b) metals;
- c) timber;
- d) polymers;
- e) stone for armouring or protection works; and
- f) bituminous materials.

Protective measures and treatments against corrosion of metals cover a wide range of methods that can be applied in the construction, operation and maintenance of maritime structures. These are also addressed in this part of <u>BS 6349</u>.

1 Scope

This part of <u>BS 6349</u> gives recommendations for the materials used in the design and construction of maritime environment structures, and includes specific provisions for use in a seawater environment.

NOTE Materials used in these conditions are often subject to more onerous environmental conditions than onshore structures, and thus particular attention is paid to the use of durable materials to provide the required performance and design life.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes provisions of this document¹). For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

Standards publications

ANSI/AWWA C217, Microcrystalline wax and petrolatum tape coating systems for steel water pipe and fittings

ASTM D1765, Standard classification system for carbon blacks used in rubber products

<u>BS 4449</u>, Steel for the reinforcement of concrete – Weldable reinforcing steel – Bar, coil and decoiled product – Specification

BS 4482, Steel wire for the reinforcement of concrete products – Specification

<u>BS 4483</u>, Steel fabric for the reinforcement of concrete – Specification

© THE BRITISH STANDARDS INSTITUTION 2021 - ALL RIGHTS RESERVED 1

¹⁾ Documents that are referred to solely in an informative manner are listed in the Bibliography.