## Vehicle restraint systems —

Part 6: Crashworthy roadside features — Impact attenuators

ICS 93.080.30



NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

This is a preview. Click here to purchase the full publication.

## Committees responsible for this Published Document

The preparation of this Published Document was entrusted by Technical Committee B/509, Road equipment, to Subcommittee B/509/1, Road restraint systems, upon which the following bodies were represented:

Aluminium Federation Association of Consulting Engineers Association of County Councils Association of Safety Fencing Contractors British Cement Association British In-situ Concrete Paving Association British Precast Concrete Federation Ltd. County Surveyors' Society Department of Transport (Highways Agency) Institution of Civil Engineers Motor Industry Research Association National Fencing Training Authority Railtrack Royal Society for the Prevention of Accidents Transport Research Laboratory **UK Steel Association** 

This Published Document, having been prepared under the direction of the Sector Committee for Building and Civil Engineering, was published under the authority of the Standards Committee and comes into effect on 15 October 1999

© BSI 10-1999

## Amendments issued since publication

Amd. No.	Date	Comments

The following BSI reference relates to the work on this publication: Committee reference B/509/1

ISBN 0 580 28253 8

This is a preview. Click here to purchase the full publication.

## Contents

	Page			
Committees responsible	Inside front cover			
Foreword	ii			
Introduction				
1 Scope	1			
2 Roadside and lorry mounted crash cushions	1			
2.1 Basic concepts of roadside crash cushions	1			
2.2 Full scale impact tests on prototype UK roadside crash	cushions 5			
2.3 Basic concepts of lorry mounted crash cushions (LMCC	8)			
2.4 Full scale impact tests on a lorry mounted crash cushio	n 11			
3 Vehicle arrester beds	13			
3.1 General	13			
3.2 Rose bush hedges	13			
3.3 Aggregate arrester beds	14			
3.4 Bull nose safety barriers	15			
4 Earth acoustic mounds as safety barriers	16			
5 Impact into utility poles	18			
Figure 1 — Deceleration for given stopping distances	3			
Figure 2 — Resistive force to decelerate vehicles of given ma	ss 3			
Figure 3 — Crash cushion impact just above bumper height	4			
Figure 4 — Labelled diagram of offset end-on crash cushion impact				
Figure 5 — Crash cushion design based on crushable diamond-shaped elements				
Figure 6 — Impact of an errant vehicle into a shadow vehicle				
Figure 7 — Effect of road tyre coefficient, $\mu$ , on shadow vehice	cle movement, D 9			
Figure 8 — Effect of impact speed on shadow vehicle movem	nent 10			
Figure 9 — Effect of errant vehicle mass on movement of sha	adow vehicle 10			
Figure 10 — Effect of shadow vehicle mass on movement of shadow vehicle				
Figure 11 — Single-track sintered fuel ash bed suitable for installation on a				
city centre hill				
Figure $12 - Full$ width sintered fuel ash bed with a low concrete barrier				
Figure 13 — Bull nose 6 m radius OBB barrier with TCB lead	-in: radial impact 16			
Figure 14 — Bull nose 6 m radius OBB barrier with TCB lead-in: parallel im				
Figure 15 — Earthbank: compacted hogging in mesh	17			
Figure 16 — Earthbank with OBB mounted at 0.6 m height				
Figure 17 — Impact into a steel column at 22.5 m/h by a 1936 Morris 8				
saloon car	18			
Figure 18 — Frangible slip base column joint	19			
Figure 19 — Deceleration curves from impacts into a slip joint column and a normal column				
Table 1 — Crash cushion impact tests (prEN 1317-3)				
Table 2 — Resistive force and stopping distance at 12 g deceleration				
Table 3 — Vehicle impact tests on crash cushions based on diamond-shaped elements				
Table 4 — Impact tests on lorry mounted crash cushions (LM	ICC) 12			
Table 5 — Comparison of calculated and test results for the movement of the shadow vehicle				
Bibliography				
Bioliography				