NA+A2:2022 to BS EN 1997-1:2004+A1:2013

Incorporating Corrigendum No. 1



BSI Standards Publication

UK National Annex to Eurocode 7: Geotechnical design – Part 1: General rules



...making excellence a habit."

This is a preview. Click here to purchase the full publication.

Publishing and copyright information

The BSI copyright notice displayed in this document indicates when the document was last issued.

© The British Standards Institution 2022 Published by BSI Standards Limited 2022

ISBN 978 0 539 19135 6

ICS 91.010.30, 93.020

The following BSI references relate to the work on this document: Committee reference B/526 Drafts for comment 14/30272166 DC, 21/30443163 DC

Publication history

First published in November 2007

Amendments/corrigenda issued since publication

Amd. no.	Date	Text affected
Corrigendum 1	31 December 2007	Reference in Table NA.1 8.6(4) changed to A.8.6 , last word of A.3.3.2 changed to "resistance" and Note A in Table A.NA.7 made same as Tables A.NA.6 and A.NA.8.
Amendment 1	31 July 2014	Implementation of national amendment A1:2014: Clause NA.1, Table NA.1 and Annex A amended.
Amendment 2	28 February 2022	Implementation of national amendment A2:2022: Table NA.1, Table A.NA.20, Table A.NA.21, NA.4 and A.6 amended.

This is a preview. Click here to purchase the full publication.

Contents

Introduction 1

NA.1 Scope 1

NA.2 Nationally Determined Parameters 2

NA.3 Decisions on the status of informative annexes 6

NA.4 References to non-contradictory complementary information 7

Bibliography 8

Annexes

Annex A (informative) Design approach and values of partial, correlation and model factors for ultimate limit states to be used in conjunction with BS EN 1997-1:2004+A1:2013 9

List of tables

Table NA.1 – Provisions of this National Annex related to Clauses in BS EN 1997-1:2004+A1:2013 where "national choice" is to be exercised 2 Table A.NA.1 – Partial factors on Actions (γ_F) for the equilibrium (EQU) limit state 10 Table A.NA.2 – Partial factors for soil parameters (γ_{M}) for the EQU limit state 10 Table A.NA.3 – Partial factors on actions (γ_F) or the effects of actions (γ_E) for the structural (STR) and geotechnical (GEO) limit states 11 Table A.NA.4 – Partial factors for soil parameters (γ_M) for the STR and GEO limit state 11 Table A.NA.5 – Partial resistance factors (γ_R) for spread footings for the STR and GEO limit states 12 Table A.NA.6 – Partial resistance factors (γ_R) for driven piles for the STR and GEO limit states 12 Table A.NA.7 – Partial resistance factors (γ_R) for bored piles for the STR and GEO limit states 13 Table A.NA.8 – Partial resistance factors (γ_R) for continuous flight auger CFA piles for the STR and GEO limit states 13 Table A.NA.9 – Correlation factors (ξ) to derive characteristic values of the resistance of axially loaded piles from static pile load tests (where n is the number of tested piles) 14 Table A.NA.10 – Correlation factors (ξ) to derive characteristic values of the resistance of axially loaded piles from ground test results (where n is the number of profiles of ground tests) 14 Table A.NA.11 – Correlation factors (ξ) to derive characteristic values of the resistance of axially loaded piles from dynamic impact tests (where n is the number of tested piles) 14 Table A.NA.13 – Partial resistance factors for retaining structures at the STR and GEO limit states 15 Table A.NA.14 – Partial resistance factors for slopes and overall stability at the STR and GEO limit states 15 Table A.NA.15 – Partial factors on actions (γ_F) at the UPL limit states 15 Table A.NA.16 – Partial factors for soil parameters (γ_M) and resistances (γ_R) at the uplift (UPL) limit state 16 Table A.NA.17 – Partial factors on actions (γ_F) at the Hydraulic Heave (HYD) limit state 16 Table A.NA.18 – Partial factors on actions and action effects for persistent and transient design situations at the ultimate limit state 17 Table A.NA.19 – Partial resistance factors ($\gamma_{a;ULS}$) for anchors in ultimate limit state for persistent and transient design situations 17 Table A.NA.20 – Values depending on anchor test method for persistent and transient design situations at the ultimate limit state and for serviceability limit states 18 Table A.NA.21 – Limiting criteria for investigation, suitability and acceptance tests for persistent and transient design situations at the ultimate and serviceability limit states 18