

PAS 128:2022

Underground utility detection, verification and location – Specification



This is a preview. [Click here to purchase the full publication.](#)

Publishing and copyright information

The BSI copyright notice displayed in this document indicates when the document was last issued.

© The British Standards Institution 2022.

Published by BSI Standards Limited 2022.

ISBN 978 0 539 21068 2

ICS 93.020 | 93.060

No copying without BSI permission except as permitted by copyright law.

Publication history

First published June 2014

Second edition April 2022

Contents

Foreword	iii
0 Introduction.....	v
1 Scope.....	1
2 Normative references	2
3 Terms, definitions and abbreviated terms	3
4 Training, qualifications and competency	5
5 Project planning	6
6 Quality level	9
7 Desktop utility records search (survey type D).....	12
8 Site reconnaissance (survey type C)	13
9 Detection (survey type B).....	15
10 Verification (survey type A)	24
11 Location	26
12 Deliverables.....	29
Annexes	
Annex A (normative)	
Buried utility detection and avoidance to support on-site permit to break ground procedures.....	32
Annex B (informative)	
Client guide to using PAS 128 and utility survey.....	34
Annex C (informative)	
Accuracy.....	40
Annex D (informative)	
Technical considerations when using utility detection methods (EML and GPR)	42
Annex E (informative)	
Example project workflow	55
Bibliography	60

List of figures

Figure C.1 – Horizontal and vertical accuracy	41
Figure D.1 – Twin aerials used to identify position	44
Figure D.2 – Estimation of depth using twin antenna	44
Figure D.3 – How GPR works	46
Figure D.4 – Relationship between frequency and wavelength	47
Figure D.5 – How GPR surveys detect linear features using parallel transects	50
Figure D.6 – How DPR surveys detect linear features using orthogonal grids	50
Figure D.7 – Choosing the appropriate frequency antenna	54
Figure E.1 – PAS 128 process flowchart	55
Figure E.2 – Survey type D process flowchart	56
Figure E.3 – Survey type C process flowchart	57
Figure E.4 – Survey type B process flowchart	58
Figure E.5 – Survey type A process flowchart	59

List of tables

Table 1 – Quality level of survey outputs	10
Table 2 – Detection methods	18
Table 3 – Other technologies	21
Table B.1 – Accuracy values	38
Table D.1 – Approximate electromagnetic properties of various materials	49

Foreword

This PAS was sponsored by the Institution of Civil Engineers (ICE). Its development was facilitated by BSI Standards Limited and it was published under licence from The British Standards Institution. It came into effect on 30 April 2022.

Acknowledgement is given to George Tuckwell (RSK) and Andy Rhoades (Buried Asset Protection Consultancy Ltd) as the technical authors, with contributions from Sam Roberts (Met Geo Environmental Ltd).

Acknowledgement is also given to the following organizations that were involved in the development of this PAS as members of the steering group:

- Chartered Institution of Civil Engineering Surveyors (CICES)
- EuroGPR
- Ordnance Survey
- The Geological Society
- The Survey Association
- Transport for London
- University of Birmingham
- Co-opted members

The following funders of this PAS are also acknowledged:

- Atkins Limited
- Catsurveys Ltd
- Chartered Institution of Civil Engineering Surveyors (CICES)
- IDS GeoRadar
- Leica Geosystems
- LinesearchbeforeUdig Ltd
- Macleod Simmonds Ltd
- Malcolm Hughes Land Surveyors
- Met Geo Environmental Ltd
- MK Surveys
- James Lewis (PAS 128 Consulting)
- Premier Energy Services Ltd
- RSK Group Ltd
- Nicholas Zembillas (Subsurface Utility Engineering)
- The Survey Association
- Utility Mapping Group UK Ltd

Acknowledgement is also given to the members of a wider review panel who were consulted in the development of this PAS.

The British Standards Institution retains ownership and copyright of this PAS. BSI Standards Limited as the publisher of the PAS reserves the right to withdraw or amend this PAS on receipt of authoritative advice that it is appropriate to do so. This PAS will be reviewed at intervals not exceeding two years.

This PAS is not to be regarded as a British Standard. It will be withdrawn in the event it is superseded by a British Standard.

The PAS process enables a specification to be rapidly developed in order to fulfil an immediate need in industry. A PAS can be considered for further development as a British Standard, or constitute part of the UK input into the development of a European or International Standard.

Supersession

This PAS supersedes PAS 128:2014, which is withdrawn.

Information about this document

This is a full revision of the PAS, and introduces the following principal changes:

- addition of guidance on training and qualifications of practitioners (Clause 4);
- updates to the application of post-processing in detection surveys (Table 2);
- new specification for buried utility detection and avoidance to support on-site permit to break ground (Annex A);
- new guidance on the accuracy of detection methods (Annex C); and
- new guidance on the technical factors that dictate the effort required for a detection survey (Annex D).

Acknowledgement is given to the following who were involved in the development of the previous edition of this PAS: Ian Bush (Black & Veatch, ICE, ICES) as the technical lead and Peter Barker (SUMO Services Ltd, The Survey Association), John Robinson (Subscan Technology Ltd) and Nick Zembillas (Subsurface Utility Engineering LLC) as the drafting panel.

This publication can be withdrawn, revised, partially superseded or superseded. Information regarding the status of this publication can be found in the Standards Catalogue on the BSI website at bsigroup.com/standards, or by contacting the Customer Services team.

Where websites and webpages have been cited, they are provided for ease of reference and are correct at the time of publication. The location of a webpage or website, or its contents, cannot be guaranteed.

Hazard warnings

WARNING 1. This PAS calls for the use of procedures that can be injurious to health if adequate precautions are not taken. It refers only to technical suitability and does not absolve the user from legal obligations relating to health and safety at any stage.

WARNING 2. For all excavations, assume that underground utilities are present and act accordingly. To avoid buried services effectively it is necessary to positively identify and locate the services that are present.

Attention is drawn to laws, rules and regulations applicable to vacuum excavating or hand digging near or atop dangerous utilities such as electric, gas, fuel or petroleum.

Attention is drawn to HSE's publication, *Avoiding danger from underground services* (HSG47) [1].

Annex A sets out the application of this specification to the detection, location and avoidance of buried services in support of excavations and intrusive ground investigations.

WARNING 3. This PAS refers to physical entry into confined spaces, which is not to be attempted without suitably trained operatives and safety equipment.

Attention is drawn to HSE's publication, *Confined spaces – A brief guide to working safely* (INDG258) [2].

Use of this document

It has been assumed in the preparation of this PAS that the execution of its provisions will be entrusted to appropriately qualified and experienced people, for whose use it has been produced.

Presentational conventions

The provisions of this PAS are presented in roman (i.e. upright) type. Its requirements are expressed in sentences in which the principal auxiliary verb is "shall".

Commentary, explanation and general informative material is presented in smaller italic type, and does not constitute a normative element.

Requirements in this PAS are drafted in accordance with *Rules for the structure and drafting of UK standards:2017*, subclause **G.1.1**, which states, "Requirements should be expressed using wording such as: 'When tested as described in Annex A, the product shall ...'". This means that only those products that are capable of passing the specified test will be deemed to conform to this PAS.

Where words have alternative spellings, the preferred spelling of the Shorter Oxford English Dictionary is used (e.g. "organization" rather than "organisation").

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

Compliance with a PAS cannot confer immunity from legal obligations.

0 Introduction

0.1 Background

As the demand on the nation's infrastructure continues to grow due to new developments, and the need to replace and/or maintain existing utilities increases, it is essential to have accurate information on the existence and location of underground utilities.

The accurate detection, identification, verification and location of utility assets have always been difficult tasks, subject to interpretation and inaccuracies. Not having sufficient or reliable information leads to:

- risk to the safety of workers and to the public;
- abortive and unnecessary work;
- damage to third party assets;
- inefficient design solutions; and
- potentially compromising the resilience of the existing network.

Accurate utility data could also afford the opportunity for as yet unrealized benefits, such as the use of remote robotic techniques to maintain asset networks in busy highways in future to reduce the need for intrusive maintenance practices (road excavations). Similarly, accurate mapping of utility networks could improve asset modelling capabilities with more determined outcomes.

NOTE *Given the wide use and varying connotations associated with the word "survey", the word "location" has been used throughout this PAS to define the act of geospatially referencing utility assets or topographical features.*

The purpose of this PAS is to set out clear and unambiguous provisions to those engaged in the detection, verification and location of active, abandoned, redundant or unknown utilities.

This PAS aims to provide:

- clarity in the service provided and methods employed;
- consistency in the approach to data capture;
- classification of the results and the confidence that can be associated with them;
- an indication of the effort required to be confident that the survey is capable in principle of achieving higher accuracy levels in different settings;

- standardization of the format of deliverables; and
- accountability for the work undertaken.

It is expected that time, education and experience in the application of this PAS will lead to more effective planning and safer execution of street works, civil works, ground works and utility-based activities.

In creating this PAS, the development of other similar work, such as guidelines and standards undertaken in the USA, Canada and Australia, have been taken into account.

Different survey types and methods provide different levels of accuracy and certainty around results. For example, verification provides more accurate results than a desktop utility records search. It is recognized that an increase in accuracy and certainty inevitably means an increase in effort, cost and time to deliver those results.

0.2 The survey type

This PAS takes a hierarchical approach to the survey types used in recognition that different clients at different stages of an asset life cycle require different levels of accuracy and confidence in the data provided. This PAS defines four types of survey:

- desktop utility records search (survey type D) – where underground utilities are identified through the collation and analysis of existing paper/online utility records;
- site reconnaissance (survey type C) – where existing records are supported and validated by the visual inspection of physical evidence observed or recorded during a site visit;
- detection (survey type B) – where underground utilities are detected and located by geophysical techniques and geospatially located; and
- verification (survey type A) – where underground utilities are observed within and located at a manhole or inspection chamber or are excavated and exposed.

These represent the different levels of survey required for obtaining information on the location of utilities, whereby the desktop utility records search usually requires the least effort and verification the most.

A survey type D is a prerequisite for survey types C, B and A. Survey type C is also a prerequisite for a survey type B but can be carried out as an independent site reconnaissance visit by the person writing the type B survey scope or as an integral part of a type B survey. Survey types A and C are independent of each other. For example, a verification survey can conform to this PAS without the need to conduct a survey type C or B, although carrying out each stage in order further reduces project risk.

More information on the different survey types is contained in Annex B.

0.3 Detection methods

This PAS defines a hierarchy of methods to be used to detect underground utilities in terms of the minimum equipment types to be used, the minimum techniques to be applied and the survey search resolution, and relates this to the maximum quality levels achievable that can be attained using a particular detection method (see Table 2 and Annex C).

The detection methods are usually selected taking into account density of services of the survey area and whether post-processing is undertaken or not. In a PAS 128 survey, both electromagnetic locators (EML) and ground penetrating radar (GPR) are deployed as a minimum in conjunction with each other for each segment of a utility within the survey area. In addition to EML and GPR, other detection methods can be applied to the survey area.

NOTE *A multiple antenna array GPR only survey can be used to increase confidence in type D information so that a more targeted type B survey can be carried out.*

By requiring the practitioner to indicate in their method statement the methodologies they intend to use and thus the level of work their price is based on, the client can assess and compare tenders on an equal basis. More importantly, this PAS defines for the practitioner the minimum standard expected for detection associated with each typical application.

0.4 Quality levels

The quality level is a classification applied to each segment of utility surveyed based on survey type undertaken (D, C, B or A), location accuracy achieved (B and A survey type), whether post-processing was undertaken and level of supporting data obtained in determining the quality level (see Table 1). It reflects the method the practitioner has used and the confidence in the accuracy at which they state they have determined the location of the service.

0.5 Absolute geospatial location of underground utilities

To improve accuracies and how data are exchanged and integrated, this PAS encourages the absolute geospatial location of utilities referenced to three dimensions using a national coordinate grid system and datum. In Great Britain this is the Ordnance Survey's National Grid (OSGB36) and Ordnance Datum Newlyn (ODN) coordinates. In Northern Ireland this is the Irish Grid (IG) as used by Ordnance Survey Northern Ireland.

NOTE *The coordinate system for Ireland is the Irish Transverse Mercator (ITM).*