

# **Sampling and examination of bituminous mixtures for roads and other paved areas —**

**Part 110: Methods of test for the  
determination of wheel-tracking rate and  
depth**

ICS 75.140; 93.080.10

# Committees responsible for this British Standard

The preparation of this British Standard was entrusted by Technical Committee B/510, Road materials, to Subcommittee B/510/1, Coated macadam and hot asphalt, upon which the following bodies were represented:

- British Civil Engineering Test Equipment Manufacturers' Association
- County Surveyors' Society
- Department of the Environment, Transport and the Regions (Highways Agency)
- Institute of Asphalt Technology
- Institute of Petroleum
- Institution of Civil Engineers
- Institution of Highways and Transportation
- Mastic Asphalt Council Ltd.
- Quarry Products Association
- Refined Bitumen Association Ltd.
- Road Surface Dressing Association
- Scottish Office (Roads Directorate)
- Society of Chemical Industry
- Transport Research Laboratory
- United Kingdom Accreditation Service

This British Standard, having been prepared under the direction of the Sector Committee for Building and Civil Engineering, was published under the authority of the Standards Committee and comes into effect on 15 November 1998

© BSI 09-1999

First published March 1996  
Second edition November 1998

The following BSI references relate to the work on this standard:  
Committee reference B/510/1  
Draft for comment 97/102878 DC

ISBN 0 580 28210 4

## Amendments issued since publication

Amd. No.	Date	Comments
10577	September 1999	Indicated by a sideline

# Contents

	Page
Foreword	ii
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Apparatus	1
5 Sampling	5
6 Preparing the test specimen	5
7 Test procedure	6
8 Calculation and expression of results	6
9 Test report	7
Annex A (informative) Precision	8
Bibliography	9
Figure 1 — Typical layout of wheel-tracking apparatus	2
Figure 2 — Typical clamping assembly and mounting table	4
Table A.1 — Precision values for wheel-tracking rate	8