Specification for mechanical and spliced joints in conveyor belting for use underground

Confirmed January 2009



ICS 53.040.20

NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

This is a preview. Click here to purchase the full publication.

Committees responsible for this British Standard

The preparation of this British Standard was entrusted to Technical Committee PRI/67, Conveyor belts, upon which the following bodies were represented:

British Rubber Manufacturers Association Ltd Health and Safety Executive Institute of Materials Tun Abdul Razak Research Centre UK Steel Association

This British Standard, having been prepared under the direction of the Materials and Chemicals Sector Policy and Strategy Committee, was published under the authority of the Standards Policy and Strategy Committee on 28 May 2002

© BSI 28 May 2002

Amendments issued since publication

	Amd. No.	Date	Comments
The following BSI references relate to the work on this British Standard: Committee reference PRI/26 Draft for comment 00/124045			
ISBN 0 580 33335 3			

This is a preview. Click here to purchase the full publication.

Contents

	Page	
Committees responsible Insid	le front cover	
Foreword	ii	
1 Scope	1	
2 Normative references	1	
3 Terms and definitions	1	
4 Mechanical fastener holding (applicable only to textile belting	g) 2	
5 Spliced/vulcanized joints (applicable to textile and steel cord of belts)	conveyor 3	
Annex A (normative) Dynamic life-test for joints made with mechanical fasteners		
Annex B (normative) Static tensile test for spliced (vulcanized) joints		
Annex C (normative) Dynamic life-test for spliced (vulcanized) joints		
Bibliography		
Figure A.1 — Symmetric geometry		
Figure A.2 — Asymmetric geometry		
Figure A.3 — Configuration of dynamic testing machine		
Table 1 — Belt test requirements (mechanical fasteners)		
Table 2 — Belt test requirements [vulcanized (spliced) joints]		
Table A.1 — Dimensions of pulley diameters and pulley centres for testing machine (see Figure A.3) relative to nominal belt strengths		
Table A.2 — Nominal loop lengths and speeds for pulley configurations		