

INTERNATIONAL STANDARD

ISO
18408

First edition
2019-08

Simplified structural design for reinforced concrete wall buildings



Reference number
ISO 18408:2019(E)

This is a preview. [Click here to purchase the full publication.](#)

© ISO 2019



COPYRIGHT PROTECTED DOCUMENT

© ISO 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword	vi
Introduction	vii
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols	3
5 Materials for reinforced concrete	6
5.1 General	6
5.2 Cement	6
5.3 Aggregates	6
5.4 Water	6
5.5 Admixtures	6
5.6 Storage of materials	6
5.7 Steel reinforcement	6
5.8 Deformed reinforcement	6
5.9 Welded-wire fabric	6
5.10 Plain reinforcement	6
5.11 Concrete mixture specification	7
6 Design and construction procedure	7
6.1 Procedure	7
6.2 Limit states	8
6.3 Ultimate limit state design format	9
6.3.1 General	9
6.3.2 Required factored strength	9
6.3.3 Design strength	9
6.4 Serviceability limit state design format	9
6.5 Design documentation	10
6.5.1 General	10
6.5.2 Calculation memoir	10
6.5.3 Geotechnical report	10
6.5.4 Structural drawings	10
6.5.5 Specifications	10
7 Limitations	11
7.1 General	11
7.2 Occupancy	11
7.3 Maximum number of storeys	11
7.4 Maximum storey height	11
7.5 Minimum wall area ratio	11
7.6 Upper limit of average shear stress	11
7.7 Maximum storey drift angle	11
8 Specific requirements	12
8.1 Structural systems	12
8.1.1 Floor system	12
8.1.2 Vertical supporting elements	12
8.1.3 Foundation	12
8.1.4 Lateral load resisting system	12
8.1.5 Other structural elements	12
8.2 General program	12
8.2.1 Architectural program	12
8.2.2 General structural requirements for the project	13
8.3 Structural layout	13

	8.3.1	General structural layout.....	13
	8.3.2	Floor planning of bearing walls.....	13
	8.3.3	Elevation planning of bearing walls.....	14
9	Actions (loads)		16
	9.1	General.....	16
	9.1.1	Load factors and load combinations.....	16
	9.2	Mass of materials.....	18
	9.3	Dead loads.....	18
	9.4	Live loads.....	19
	9.5	Specified snow load.....	19
	9.6	Specified wind forces.....	19
	9.7	Specified earthquake forces.....	19
	9.7.1	General.....	19
	9.7.2	Seismic hazard.....	20
	9.7.3	No seismic hazard zones:.....	20
	9.7.4	Low seismic hazard zones:.....	20
	9.7.5	Intermediate seismic hazard zones:.....	20
	9.7.6	High seismic hazard zones:.....	20
	9.7.7	Soil profile types.....	26
	9.7.8	Site effects.....	27
	9.7.9	Design response spectral ordinates.....	27
	9.8	Seismic design base shear.....	27
	9.8.1	Seismic-resistant structural system.....	27
	9.8.2	Energy-dissipation capacity of the seismic-resistant structural system.....	28
	9.8.3	Computation of the seismic design base shear.....	28
	9.8.4	Vertical distribution of the design seismic forces and the design storey shear forces.....	28
10	Analysis		28
	10.1	Method of analysis for moment, shear and axial force of members.....	28
	10.1.1	General.....	28
	10.1.2	Simplified method.....	29
	10.2	Method of analysis for storey drift angle.....	33
	10.2.1	General.....	33
	10.2.2	Simplified method.....	33
11	Structural concrete walls		34
	11.1	General.....	34
	11.2	Design load definition.....	34
	11.3	Dimensional guides.....	34
	11.3.1	General.....	34
	11.3.2	Limiting dimensions.....	34
	11.4	Details of reinforcement.....	35
	11.4.1	General.....	35
	11.4.2	Shear reinforcement.....	36
	11.4.3	Flexural reinforcement.....	37
12	Wall girders		38
	12.1	General.....	38
	12.2	Design strength.....	38
	12.2.1	Flexural strength.....	38
	12.2.2	Shear strength.....	38
	12.3	Details of reinforcement.....	39
	12.3.1	General.....	39
	12.3.2	Vertical reinforcement.....	39
	12.3.3	Longitudinal reinforcement.....	40
13	Wall — Wall girder joints		41
	13.1	General.....	41
	13.2	Design strength.....	41

13.3	Development length for reinforcing bars.....	42
13.4	Details of reinforcement.....	43
14	Floor slab.....	43
14.1	General.....	43
14.2	Design load definition.....	43
14.2.1	Loads to be included.....	43
14.2.2	Dead load and live load.....	43
14.2.3	Factored design load.....	43
14.3	Two-way solid slabs supported on wall girders or structural concrete walls.....	43
14.3.1	Dimensional guides.....	43
14.3.2	Design strength.....	44
14.3.3	Design bending moment.....	45
14.4	End anchorage of reinforcement.....	46
15	General reinforced concrete requirements.....	46
15.1	General.....	46
15.2	Cover concrete depth.....	46
15.2.1	Minimum concrete cover.....	46
15.2.2	Special fire protection.....	48
15.2.3	Special corrosion protection.....	48
15.3	Minimum and maximum reinforcement bar diameter.....	48
15.4	Minimum reinforcement bend diameter.....	49
15.5	Standard hook dimensions.....	49
15.6	Bar separation and maximum aggregate size.....	50
15.6.1	General.....	50
15.6.2	Maximum nominal coarse aggregate size.....	50
15.6.3	Minimum clear spacing between parallel bars in a layer.....	51
15.6.4	Minimum clear spacing between parallel layers of reinforcement.....	51
15.6.5	Clear spacing between parallel lap splices.....	51
15.7	Development length, lap splicing and anchorage of reinforcement.....	51
15.7.1	Development length.....	51
15.7.2	Lap splice dimensions.....	53
15.7.3	Minimum standard hook anchorage distance.....	54
16	Foundations.....	54
16.1	Dimensioning of the foundation elements.....	54
16.2	Footings.....	55
16.2.1	Moment in footings.....	55
16.2.2	Shear in footings.....	55
16.2.3	Development of reinforcement in footings.....	55
16.2.4	Minimum footing depth.....	56
16.2.5	Transfer of forces at base of column, wall or reinforced pedestal.....	56
16.2.6	Sloped or stepped footings.....	56
16.3	Foundation mats.....	56
16.4	Footings on piles.....	56
16.4.1	General.....	56
16.4.2	Anchorage of reinforcement.....	56
16.4.3	Maximum axial stresses.....	56
16.4.4	Reinforcement minimum ratios and lengths.....	57
16.5	Foundation beams.....	57
16.5.1	Dimensional guides.....	57
16.5.2	Longitudinal reinforcement.....	57
16.5.3	Transverse reinforcement.....	57
	Bibliography.....	58

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 71, *Concrete, reinforced concrete and pre-stressed concrete*, Subcommittee SC 5, *Simplified design standard for concrete structures*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

This document aims to provide rules for the design and construction of reinforced concrete (RC) wall structures. The design rules are based on the ratio of wall cross-sectional area to the floor area. Therefore, actions (loads) and simplified analysis procedures are included as well as minimum acceptable construction practice guidelines.

Reinforced concrete wall buildings (WRC) consist of bearing walls, wall girders, slabs, footing girders and foundations. These buildings have excellent seismic performance and fire-resistance and are low-priced construction compared to frame structures. This type of structure is one of the most popular buildings for residential apartment houses in the world.

Structural features of WRC buildings can be summarized as follows:

- high seismic performance (according to the damage of the past earthquakes, the damage ratio of WRC structures is much smaller than that of other types of structures);
- fire resistance (the performance is as good as that of RC buildings);
- economical superiority (bearing walls are as thick as wall girders).

Buildings designed according to this document will consequently:

- a) for moderate earthquake motions, not produce cracks on bearing walls.
- b) for extremely large earthquake motions, prevent from collapse and fall.

The characteristics of this document to achieve the above performances are as follows:

- 1) Prevention of shear cracks developing in bearing walls during moderate earthquake motions

The shear stress intensity in bearing walls during moderate earthquake motions on every storey and in every direction should be less than shear cracking stress of concrete being used, in order not to produce cracks in the bearing walls.

Seismic shear force on every storey and in every direction should be set forth corresponding to moderate earthquake motions.

- 2) Prevention of buildings collapsing during extremely large earthquake motions

The design storey shear force should be set forth corresponding to extremely large earthquake motions. However, this magnitude is reduced, considering the ductility of structures. The reduction value may be about 0,5 for this type of structures. Finally, for example, this magnitude for the first storey almost corresponds to half of the total weight of a building.

In order to secure the structural safety in case of such storey shear, some structural specifications are prescribed in the structural design. The upper limits of average shear stress as well as the maximum storey drift angle are defined in order to control the shearing stress of the wall during the extremely large earthquake motions. That is one of such important specifications. Also, steel bar arrangement specifications and bearing wall arrangement/configuration, etc., are very important specifications to secure structural safety.

This document contains provisions that can be modified by the National Standards Body due to local design and construction requirements and practices. The specifications that can be modified are indicated using ["boxed values"]. The National Standards Body is expected to review the "boxed values" and may substitute alternative definitive values for these elements for use in the national application of this document.