



JAPANESE
INDUSTRIAL
STANDARD

Translated and Published by
Japanese Standards Association

JIS A 6207 : 2006
(JST/JSA)

Silica fume for use in concrete

ICS 91.100.30

Reference number : JIS A 6207 : 2006 (E)

Foreword

This translation has been made based on the original Japanese Industrial Standard revised by the Minister of Economy, Trade and Industry through deliberations at the Japanese Industrial Standards Committee as the result of proposal for revision of Japanese Industrial Standard submitted by Japan Silica Fume Technology Associates (JST) / Japanese Standards Association (JSA), with the draft being attached, based on the provision of Article 12 Clause 1 of the Industrial Standardization Law applicable to the case of revision by the provision of Article 14.

Consequently **JIS A 6207:2000** is replaced with this Standard.

Attention is drawn to the possibility that some parts of this Standard may conflict with a patent right, application for a patent after opening to the public, utility model right or application for registration of utility model after opening to the public which have technical properties. The relevant Minister and the Japanese Industrial Standards Committee are not responsible for identifying the patent right, application for a patent after opening to the public, utility model right or application for registration of utility model after opening to the public which have the said technical properties.

Date of Establishment: 2000-07-20

Date of Revision: 2006-03-25

Date of Public Notice in Official Gazette: 2006-03-27

Investigated by: Japanese Industrial Standards Committee
Standards Board

Technical Committee on Civil Engineering

JIS A 6207 : 2006, First English edition published in 2006-11

Translated and published by: Japanese Standards Association
4-1-24, Akasaka, Minato-ku, Tokyo, 107-8440 JAPAN

In the event of any doubts arising as to the contents,
the original JIS is to be the final authority.

© JSA 2006

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

SI/HN

Contents

	Page
Introduction	1
1 Scope	1
2 Normative references	1
3 Definitions	2
4 Classification	2
5 Quality	3
5.1 Quality of powdery silica fume and granular silica fume	3
5.2 Quality of silica fume slurry	3
6 Sample	3
6.1 Sampling	3
6.2 Preparation	3
7 Test method	4
7.1 Silicon dioxide	4
7.2 Magnesium oxide	4
7.3 Sulphur trioxide	4
7.4 Free calcium oxide	4
7.5 Free silicon	4
7.6 Chloride ion	4
7.7 Ignition loss	4
7.8 Humidity	4
7.9 Specific surface area	4
7.10 Density	4
7.11 Activation index	4
7.12 Solid content in silica fume slurry	4
8 Inspection	4
9 Packaging	4
10 Marking	4
11 Report	5
Annex 1 (normative) Determination method of solid content in silica fume slurry	7
Annex 2 (normative) Determination method of free calcium oxide	8
Annex 3 (normative) Testing method of density of silica fume by using volumetric flask	11
Annex 4 (normative) Testing method of activation index of silica fume based on mortar	13