

Detection and Mitigation of Stray-Current Corrosion of Reinforced and Prestressed Concrete Structures

This NACE International (NACE) standard represents a consensus of those individual members who have reviewed this document, its scope, and provisions. Its acceptance does not in any respect preclude anyone, whether he or she has adopted the standard or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not in conformance with this standard. Nothing contained in this NACE standard is to be construed as granting any right, by implication or otherwise, to manufacture, sell, or use in connection with any method, apparatus, or product covered by letters patent, or as indemnifying or protecting anyone against liability for infringement of letters patent. This standard represents minimum requirements and should in no way be interpreted as a restriction on the use of better procedures or materials. Neither is this standard intended to apply in all cases relating to the subject. Unpredictable circumstances may negate the usefulness of this standard in specific instances. NACE assumes no responsibility for the interpretation or use of this standard by other parties and accepts responsibility for only those official NACE interpretations issued by NACE in accordance with its governing procedures and policies which preclude the issuance of interpretations by individual volunteers.

Users of this NACE standard are responsible for reviewing appropriate health, safety, environmental, and regulatory documents and for determining their applicability in relation to this standard prior to its use. This NACE standard may not necessarily address all potential health and safety problems or environmental hazards associated with the use of materials, equipment, and/or operations detailed or referred to within this standard. Users of this NACE standard are also responsible for establishing appropriate health, safety, and environmental protection practices, in consultation with appropriate regulatory authorities if necessary, to achieve compliance with any existing applicable regulatory requirements prior to the use of this standard.

CAUTIONARY NOTICE: NACE standards are subject to periodic review and may be revised or withdrawn at any time in accordance with NACE technical committee procedures. NACE requires that action be taken to reaffirm, revise, or withdraw this standard no later than five years from the date of initial publication and subsequently from the date of each reaffirmation or revision. The user is cautioned to obtain the latest edition. Purchasers of NACE standards may receive current information on all standards and other NACE publications by contacting the NACE *First*Service Department, 15835 Park Ten Place, Houston, TX 77084-5145 (telephone +1 281-228-6200 or at first.service@nace.org).

ABSTRACT

This NACE International standard practice establishes the general principles to be adopted to minimize the effects of stray current corrosion caused by direct current (DC) and/or alternating current (AC) from external sources on steel reinforced concrete (RC) and prestressed concrete (PC) structures or structural elements. The standard practice offers guidance for the design of concrete structures that may be subject to stray-current corrosion; the detection of stray current interference; the selection of protection measures; and the selection of mitigation methods. The standard practice is intended for use by designers of RC and PC structures, professionals working with electrochemical techniques (e.g., cathodic protection [CP], realkalization, and electrochemical chloride extraction [ECE]); owners of structures with the risk of reinforcement corrosion caused by stray currents; owners of systems that could generate stray currents to concrete structures; engineers; and other interested parties.

KEYWORDS

alternating current (AC), cathodic protection (CP), concrete, corrosion, direct current (DC), electrochemical chloride extraction (ECE), electrochemical techniques, grounding, impressed current cathodic protection (ICCP), IR-free potential, NACE Publication 01110, NACE SP0177, NACE SP0290, prestressed concrete (PC), potential interference, rail transit, realkalization, reinforcement corrosion, sacrificial anodes, static stray currents, steel reinforced concrete (RC), STG 01, stray Stray Current Corrosion, currents, stray-current mitigation, telluric currents, TG 356.

©2019 NACE International, 15835 Park Ten Place Suite 200 Houston TX 77084 USA All rights reserved Repro-

Foreword

This NACE International standard practice establishes the general principles to be adopted in order to minimize the effects of stray current corrosion caused by direct current (DC) and/or alternating current (AC) from external sources on steel reinforced concrete (RC) and prestressed concrete (PC) structures or structural elements. The standard practice is intended to offer guidance for: the design of concrete structures that may be subject to stray-current corrosion; the detection of stray current interference; the selection of appropriate protection measures; and the selection of appropriate mitigation methods.

The standard practice is intended for use by designers of RC and PC structures, professionals dealing with electrochemical techniques (e.g., cathodic protection [CP], realkalization, and electrochemical chloride extraction [ECE]), owners of structures with the risk of reinforcement corrosion caused by stray currents, owners of systems that could generate stray currents to concrete structures, engineers, and other interested parties.

The technical background for this standard is published as NACE Publication 01110, prepared by Task Group (TG) 356.1

This standard practice was prepared in 2019 by NACE TG 356, "Reinforced Concrete: Stray-Current-Induced Corrosion." This TG is administered by Specific Technology Group (STG) 01, "Reinforced Concrete"; and is sponsored by STG 05, "Cathodic/ Anodic Protection." This standard practice is issued by NACE International under the auspices of STG 01.

In NACE standards, the terms *shall, must, should,* and *may* are used in accordance with the definitions of these terms in the NACE Publications Style Manual. The terms *shall* and *must* are used to state a requirement, and are considered mandatory. The term *should* is used to state something good and is recommended, but is not considered mandatory. The term *may* is used to state something considered optional.

NACE International ©2019 NACE International, 15835 Park Ten Place, Suite 200, Houston TX 77084, USA. All rights reserved.

Detection and Mitigation of Stray-Current Corrosion of Reinforced and Prestressed Concrete Structures

1.	General	4
2.	Definitions	5
3.	Stray Current Identification and Mitigation During the Design Stage	5
4.	Stray Current Detection Methods	7
5.	Monitoring of Stray-Current Interference	9
6.	Stray-Current Mitigation in Existing Structures	. 10
7.	Inspection and Maintenance of a Stray Current Control System	. 12
8.	Records File	. 13
	References	. 13

3